

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. ~~Section~~
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Matador Operating Company

3. Address and Telephone No.

8340 Meadow Rd, #158, Dallas, TX 75231, 214-987-3650

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

735' FNL; 660' FWL, Sec 30, 18S-33E

5. Lease Designation and Serial No.
LC069276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hudson Federal 30 #4

9. API Well No.

30-025-34301

10. Field and Pool, or Exploratory Area

South Corbin Woflcamp

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Spud & surface csg
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded well @ 8:00 AM MST 2-21-98. Drill to 396'. Ran 9 jts 13-3/8" 48# H-40 STC csg. Tally 400.22, set @ 396. Halliburton cmt w/ lead 115 sx Permian Basin Filler @ 11.7 PPG, 2.89 CFS yld. Tail 200 sx C w/ 2% CaCl2 @ 14.6 PPG @ 1.34 CFS yld. Had full returns thru-out & circ 40 sx to pit. Bump plug & floats held. WOC. Cut off csg & weld on 13-5/8 3M x 13-3/8" SOW csghd. NU 5M double ram BOP w/ Hydril. Test to 1500 psi. OK.

ACCEPTED FOR RECORD

FEB 26 1998

BLM

14. I hereby certify that the foregoing is true and correct

Signed

[Signature]

Title

Drilling Manager

Date

2-23-98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side