

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-34392
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. V-2040
Lease Name or Unit Agreement Name Fontaine 28 State Com
Well No. 1
Pool name or Wildcat La Rica Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Matador Operating Company	
Address of Operator 8340 Meadow Rd #158, Dallas, TX 75231	
Well Location Unit Letter <u>N</u> <u>1200</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>28</u> Township <u>18S</u> Range <u>34E</u> NMPM <u>Lea</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 4027	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: Operator Change ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Matador Operating Company took over operations from Heyco @ 6:00 PM 8-3-98. Well had been drilled to 13,726'. Matador ran 5-1/2" 17# csg. Set @ 13,727. Cmt 1st stg: test lines 3000#, 10 bbl FW, 12 bbl mud flush, 10 bbl FW, 550 sxs Super Modified H w/ .4% CFR-3, .5% Halad 344, 1# salt, 5# Gilsonite, 13# wt, 1.65 yld displaced w/ 315 bbls. Bumped plug @ 12:45 PM. Cycle DV tool & circ. Recovered wtr & flush-tr cmt. 2nd stg: 20 FW, 715 sxs Lead: Interfill H w/ 5# Gilsonite, 11.8 wt, 2.53 yld. Tail 100 sxs poz neat 15.6 w/ 1.18 yld, displace w/ 242 bbls. Bumped plug @ 8:00 PM. Pressure up, float held. Install tbg head, test to 2500# OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John W. Bell TITLE Drilling Manager DATE 8-25-97
TYPE OR PRINT NAME John W. Bell 214-987-7144 TELEPHONE NO.

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: