## State of New Mexico Energy, minerals and Natural Resources Department

2040 Pag	VATION DIVISION theco St. , NM 87505	WELL API NO.  30-025-34508  sindicate Type of Lease
<u>DISTRICT III</u> 1000 Rio Brazos Rd., Aztec, NM 87410		STATE X FEE State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DIFFERENT RESERVOIR. USE "APPLICATION (FORM C-101) FOR SUCH PROPOSA	DEEPEN OR PLUG BACK TO A	rLease Name or Unit Agreement Name
Type of Well: OIL GAS WELL WELL X OTHER		Zafiro State "35" Com
Matador Operating Company		NVeil No.
**SAddress of Operator 8340 Meadow Rd., #158, Dallas,	TX 75231	Pool name or Wildcat WEST La Rica Mrw/E K BS
Well Location  Unit Letter G 2310 Feet From The North Line and 1980 Feet From The East Line		
Section 32 Township 18S	Range 34E	NMPM Lea County
neElevation (Show was 3 9 0 1	nether DF, RKB, RT, GR, etc. GL	
11 Check Appropriate Box to India	cate Nature of Notice, Rep	port, or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OF	NS. PLUG AND ANBANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT JOB		
OTHER:	OTHER:	
naDescribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.		
TD 7-7/8" hole @ 13,650' 9:15 AM 10-23-98. Ran logs: GR-DLL-MCGD-LSS; GR-SDL-DSN & SRT. Recovered sidewall cores. Ran 68 jts 5-1/2" 17# M-95 and 263 jts 5-1/2" 17# L-80 csg. Set @ 13,650'. Cmt w/ 20 bbls FW, 900 sxs Super modified "H" w/ .35% CFR-3, .4% Halad-344, 4% salt, .2% HR-7 yld 1.70, wt 13#. Displace w/ 315 bbls FW. Bump plug @ 12:00. Float held. ND & set slips. Install tbg head.		
SDL-DSN & SRT. Recovered s 263 jts 5-1/2" 17# L-80 csg. Se modified "H" w/ .35% CFR-3, . 13#. Displace w/ 315 bbls FW.	sidewall cores. Ran 68 jts t @ 13,650'. Cmt w/ 20 b 4% Halad-344, 4% salt, .2	5-1/2" 17# M-95 and bls FW, 900 sxs Super % HR-7 vld 1.70, wt
SDL-DSN & SRT. Recovered so 263 jts 5-1/2" 17# L-80 csg. Se modified "H" w/ .35% CFR-3, . 13#. Displace w/ 315 bbls FW. slips. Install tbg head.	sidewall cores. Ran 68 jts to a 13,650'. Cmt w/ 20 b 4% Halad-344, 4% salt, .2 Bump plug @ 12:00. Floor with the same and belief.  mreDrilling M	5-1/2" 17# M-95 and bls FW, 900 sxs Super % HR-7 yld 1.70, wt eat held. ND & set  anager DATE
SDL-DSN & SRT. Recovered so 263 jts 5-1/2" 17# L-80 csg. Se modified "H" w/ .35% CFR-3, . 13#. Displace w/ 315 bbls FW. slips. Install tbg head.  Thereby certify that the information above is true and complete to the best of m signature  Typeor print name John W. Bell	sidewall cores. Ran 68 jts to a 13,650'. Cmt w/ 20 b 4% Halad-344, 4% salt, .2 Bump plug @ 12:00. Floor knowledge and belief.	5-1/2" 17# M-95 and bls FW, 900 sxs Super % HR-7 yld 1.70, wt eat held. ND & set  anager
SDL-DSN & SRT. Recovered so 263 jts 5-1/2" 17# L-80 csg. Se modified "H" w/ .35% CFR-3, . 13#. Displace w/ 315 bbls FW. slips. Install tbg head.	sidewall cores. Ran 68 jts to a 13,650'. Cmt w/ 20 b 4% Halad-344, 4% salt, .2 Bump plug @ 12:00. Floor with the same and belief.  mreDrilling M	5-1/2" 17# M-95 and bls FW, 900 sxs Super % HR-7 yld 1.70, wt eat held. ND & set
SDL-DSN & SRT. Recovered so 263 jts 5-1/2" 17# L-80 csg. Se modified "H" w/ .35% CFR-3, . 13#. Displace w/ 315 bbls FW. slips. Install tbg head.  Thereby certify that the information above is true and complete to the best of m signature  Typeor print name John W. Bell	sidewall cores. Ran 68 jts to a 13,650'. Cmt w/ 20 b 4% Halad-344, 4% salt, .2 Bump plug @ 12:00. Floor with the same and belief.  mreDrilling M	5-1/2" 17# M-95 and bls FW, 900 sxs Super % HR-7 yld 1.70, wt eat held. ND & set