

Chevron

Monument 36 State #2 - I 36-183-36c
SUR: 1632 / S 4 1298 / E
BHL: 1601 / S 4 1070 / E

Directional Survey Data

Version 1

TARGET: 90 (AZMUTH) METHOD OF MINIMUM RADIUS OF CURVATURE CALCULATION: CORRECTION: 8.47

DATE	MEASURED DEPTH	TVD	ANGLE	DIRECTION AZMUTH	VERTICAL SECTION	COORDINATES		DOG LEG SEVERITY	INITIALS	REMARKS
						N or S	E or W			
	0	0.00	0.00	0.0	0.00	N 0.00	E 0.00	0.00		THIS LINE IS ENTRY ONLY
	235	234.99	0.75	2.0	0.05	N 1.54	E 0.05	0.32		
	475	474.97	1.00	346.0	-0.40	N 5.14	W 0.40	0.14		
	708	707.94	1.00	41.0	0.44	N 8.65	E 0.44	0.40		
	962	961.91	1.00	304.0	0.06	N 11.56	E 0.06	0.59		
	1,217	1,216.88	1.00	350.0	-2.17	N 14.99	W 2.17	0.31		
	1,406	1,405.86	0.50	334.0	-2.82	N 17.36	W 2.82	0.28		
	1,841	1,840.82	1.25	68.0	0.75	N 20.84	E 0.75	0.32		
	2,161	2,160.76	1.00	34.0	5.55	N 24.47	E 5.55	0.22		
	2,638	2,637.51	2.75	87.0	19.30	N 28.52	E 19.30	0.48		
	2,797	2,796.30	3.25	63.0	27.13	N 30.76	E 27.13	0.84		
	2,955	2,954.09	3.00	106.0	35.09	N 31.66	E 35.09	1.46		
	3,178	3,176.77	3.25	77.0	46.86	N 31.47	E 46.86	0.71		
	3,430	3,428.43	2.75	99.0	59.80	N 32.13	E 59.80	0.49		
	3,653	3,651.14	3.25	73.0	71.12	N 33.14	E 71.12	0.64		
	3,875	3,873.01	3.25	231.0	72.25	N 31.02	E 72.25	2.87		
	4,097	4,094.87	3.00	6.0	67.97	N 32.84	E 67.97	2.60		
	4,317	4,314.65	3.25	97.0	74.76	N 37.81	E 74.76	2.03		
	4,570	4,567.24	3.25	97.0	89.00	N 36.06	E 89.00	0.00		
	4,825	4,821.81	3.50	121.0	102.84	N 31.17	E 102.84	0.56		
	5,080	5,076.38	3.25	101.0	116.61	N 25.78	E 116.61	0.47		
	5,372	5,367.91	3.25	89.0	133.01	N 24.34	E 133.01	0.23		
	5,624	5,619.57	2.75	111.0	145.80	N 22.30	E 145.80	0.49		
	5,877	5,872.28	2.75	117.0	156.87	N 17.37	E 156.87	0.11		
	6,131	6,125.91	3.50	129.0	168.33	N 9.73	E 168.33	0.39		
	6,353	6,347.60	2.50	123.0	177.66	N 2.83	E 177.66	0.47		
FIELD	6,575	6,569.37	2.75	104.0	186.88	S 1.10	E 186.88	0.41		
Goodwin (Abn)		LEASE		Monument State 36		WELL #		2	PAGE	1 OF ONE

[illegible]