

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.
30-025-34612
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Lease Name or Unit Agreement Name Laney "A"			
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐	8. Well No. 2			
2. Name of Operator EnerQuest Resources, LLC	9. Pool name or Wildcat East Hobbs (San Andres)			
3. Address of Operator P. O. Box 11150, Midland, TX 79702				
4. Well Location Unit Letter <u>0</u> : <u>853</u> Feet From The <u>south</u> Line and <u>1980</u> Feet From The <u>east</u> Line Section <u>30</u> Township <u>18S</u> Range <u>39E</u> NMPM Lea County				
10. Date Spudded 5-20-99	11. Date T.D. Reached 5-27-99	12. Date Compl. (Ready to Prod.) 6-05-99	13. Elevations (DF & RKB, RT, GR, etc.) 3606' GR	14. Elev. Casinghead 3606'
15. Total Depth 4615'	16. Plug Back T.D. 4610'	17. If Multiple Compl. How Many Zones? NA	18. Intervals Drilled By Rotary Tools ☒ Cable Tools ☐	20. Was Directional Survey Made Yes
19. Producing Interval(s), of this completion - Top, Bottom, Name 4499' - 4603' San Andres				22. Was Well Cored No
21. Type Electric and Other Logs Run GR-CNL-LDT-DLL-MSFL				

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24	1925	12 1/4"	825 sks "C"	0
5 1/2"	15.50	4615	7 7/8"	485 sks "C"	0

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8	4520	NA

26. Perforation record (interval, size, and number) 4499-4603, 0.5", 52 perforations	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	4499-4603	2250 gals 15% NEFE HCL


PRODUCTION

28. Date First Production 6-06-99	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping, 1 1/2" Insert					Well Status (Prod. or Shut-in) Prod	
Date of Test 6-15-99	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 22	Gas - MCF 9	Water - Bbl. 184	Gas - Oil Ratio 409
Flow Tubing Press. NA	Casing Pressure 17 psi	Calculated 24-Hour Rate	Oil - Bbl. 22	Gas - MCF 9	Water - Bbl. 184	Oil Gravity - API - (Corr.) 31	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold to GPM						Test Witnessed By Jerry Guy, Hobbs, NM	

30. List Attachments

Deviation Survey Record, GR-CNL-LDT-DLL-MSFL logs

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature  Printed Name Christopher P. Renaud Title Vice President Date 6-17-99

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anyh	1841	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt		T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	3006	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	3472	T. Devonian	T. Menefee	T. Madison
T. Queen	3712	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	4260	T. Montoya	T. Mancos	T. McCracken
T. San Andres	4434	T. Simpson	T. Gallup	T. Ignacio Ozite
T. Glorieta		T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T.
T. Blinberry		T. Gr. Wash	T. Morrison	T.
T. Tubb		T. Delaware Sand	T. Todillo	T.
T. Drinkard		T. Bone Springs	T. Entrada	T.
T. Abo			T. Wingate	T.
T. Wolfcamp			T. Chinle	T.
T. Penn			T. Permian	T.
T. Cisco (Bough C)			T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	4434	No. 3, from	No. 4, from	No. 2, from
	4575			

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	feet	No. 2, from	feet	No. 3, from	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology
Suff	1841	1841	Red Beds
1841	3006	1165	Argy & Salt
3006	3106	100	Sd, sh, anhy & salt
3106	3472	366	Argy, salt & dol
3472	3964	492	Sd, anhy & sh
3964	4260	296	Argy, sd
4260	4405	145	Argy, dol & sh
4405	4434	29	Sandy dol
4434	4615	181	Dol