

Submit 3 Copies To Appropriate
District Office
DISTRICT I
1625 N. French Dr., Hobbs, NM 88240
DISTRICT II
811 South First, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 S. Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-025-34787

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

24182

7. Lease Name or Unit Agreement Name:

Laney Reese

8. Well No. 3

9. Pool name or Wildcat
Hobbs San Andres East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Lynx Energy Company, Inc.

3. Address of Operator

2121 San Jacinto, Ste 860, LB 52, Dallas, TX 75201

4. Well Location I 1650 South 330 East
Unit letter : feet from the line and feet from the line
30 18S 39E Lea
Section Township Range NMPM County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3614' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND
ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Spud well 12:45 pm, 12/26/99. Set surface casing 12/27/99. Ran 43 jts. 8-5/8", 24#, J-55, sT&c casing to 1911' and cemented w/ 700 sx Lite P-Plus, 2% CaCl, 0.25#/sk Flocele; tailed w/ 125 sx Premium, 2% CaCl, 0.25#/sk Flocele. Plug down 3:04 am, 12/28/99, Circ 90 sx to surface. Drilled 7-7/8" hole to 4627'. Ran 109 jts. 5-1/2", 15.5#, J-55, 8rd, lT&c casing to 4627' and cemented with 75 sx Scavenger cement, 350 sx Class C Interfill and 160 sx Class H. Plug down 6:30 am, 01-02-2000.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Dana Pearce TITLE _____ DATE 01/12/2000

Type or print name Dana Pearce Production Secretary Telephone No. 214/969-5555x239

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

5
C