


**DRILLING CONTROL
CONDITION II-B 3000 WP
FOR AIR DRILLING OR
WHERE NITROGEN OR AIR BLOWS ARE EXPECTED**

H₂S TRIM REQUIRED
YES _____ NO X



DRILLING CONTROL

MATERIAL LIST - CONDITION II - B

- | | |
|----------------|---|
| A | Texaco Wellhead |
| B | 1000# W.P. drilling spool with a 2" minimum flanged outlet for Kill line and 3" minimum flanged outlet for choke line. |
| C | 1000# W.P. dual ram type preventer, hydraulic operated with 1" steel, 1000# W.P. control lines (where sub-structure height is adequate, 1 - 1000# W.P. single ram type preventers may be utilized). |
| D | Rotating Head with fill up outlet and extended Bloode Line. |
| 1, 3, 4, 7, 8, | 2" minimum 1000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 2 | 3" minimum 1000# W.P. back pressure valve. |
| 3, 4, | 1" minimum 1000# W.P. flanged full opening steel gate valve, or Halliburton Lo Torc Plug valve. |
| 12 | 3" minimum schedule 80, Grade "A", seamless line pipe. |
| 13 | 2" minimum x 3" minimum 1000# W.P. flanged cross. |
| 10, 11 | 2" minimum 1000# W.P. adjustable choke bodies. |
| 14 | Cameron Mud Gauge or equivalent (location optional in choke line). |
| 15 | 2" minimum 1000# W.P. flanged or threaded full opening steel gate valve, or Halliburton Lo Torc Plug valve. |



TEXACO, INC.
MIDLAND DIVISION
MIDLAND, TEXAS



EXHIBIT C

SCALE	DATE	EST. NO.	ORG. NO.
DRAWN BY			
CHECKED BY			
APPROVED BY			