

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-34955
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-4226
7. Lease Name or Unit Agreement Name Central EK Queen Unit
8. Well No. 17
9. Pool name or Wildcat EK Yates-SR-Queen

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Seely Oil Company	
3. Address of Operator 815 W. 10th St., Fort Worth, Tx. 76102	
4. Well Location Unit Letter <u>M</u> : <u>990</u> Feet From The <u>West</u> Line and <u>853</u> Feet From The <u>South</u> Line Section <u>7</u> Township <u>18S</u> Range <u>34E</u> NMPM <u>Lea</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4091' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Subject well was drilled to a total depth of 4504'. 5-1/2" 17#/ft. J-55 csg. was run to a total depth of 4504' and cemented w/300 sxs. Class C 35/65 Pozmix followed by 410 sxs. 50/50 Clash H Pozmix w/6# salt/sx. & 1/2% friction reducer. Plug down @ 11:30 p.m. 4/15/2000. Tested csg. to 2500 psi prior to releasing pressure.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David L. Henderson TITLE Petroleum Engineer DATE 4/17/00
TYPE OR PRINT NAME David L. Henderson TELEPHONE NO. 817/332-1377

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

5
C