

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	1435	T. Canyon	11675
T. Salt	1560	T. Strawn	12120
B. Salt	2880	T. Atoka	12510
T. Yates	3120	T. Miss	
T. 7 Rivers	3540	T. Devonian	
T. Queen	4235	T. Silurian	
T. Grayburg	4750	T. Montoya	
T. San Andres		T. Simpson	
T. Glorieta		T. McKee	
T. Paddock		T. Ellenburger	
T. Blinberry		T. Gr. Wash	
T. Tubb		T. Delaware Sand	5600
T. Drinkard		T. Bone Springs	7485
T. Abo		T. Morrow Clastics	13050
T. Wolfcamp	10720	T. U. Miss	13640
T. Penn	11440	T.	
T. Cisco (Bough C)		T.	
		T. Ojo Alamo	
		T. Kirtland-Fruitland	
		T. Pictured Cliffs	
		T. Cliff House	
		T. Menefee	
		T. Point Lookout	
		T. Mancos	
		T. Gallup	
		Base Greenhorn	
		T. Dakota	
		T. Morrison	
		T. Todilto	
		T. Entrada	
		T. Wingate	
		T. Chinle	
		T. Permian	
		T. Penn "A"	
		T. Penn "B"	
		T. Penn "C"	
		T. Penn "D"	
		T. Leadville	
		T. Madison	
		T. Elbert	
		T. McCracken	
		T. Ignacio Otzte	
		T. Granite	
		T.	
		T.	
		T.	
		T.	
		T.	
		T.	
		T.	
		T.	
		T.	
		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from 11065 to 11120 oil
 No. 2, from 13290 to 13525 gas
 No. 3, from to
 No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
 No. 2, from to feet
 No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1435	1435	Red Beds				
1435	3115	1680	Anhydrite & Salt				
3115	4700	1585	Dolomite, Anhydrite & Sd				
4700	5600	900	Dolomite & Sd				
5600	7440	1840	Sandstone				
7440	8770	1330	Limestone, Shale & Chert				
8770	10750	1980	Sandstone & LS & Dol				
10750	11450	700	Limestone & Shale				
11450	12100	650	Shale & Limestone				
12100	12510	410	Limestone				
12510	12790	280	Shale, Sand & Limestone				
12790	13050	260	Limestone, Shale & Chert				
13050	13640	590	Sandstone, Shale & Limestone				
13640	13700	60	Shale & Limestone				