

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. C Cons. Division
1625 N. French Dr
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Lease Designation and Serial No.
LC 069276

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
Oil Well ☐ Gas Well ☒ Other ☐
2. Name of Operator
Nearburg Producing Company
3. Address and Telephone No.
3300 North A Street, Building 2, Suite 120, Midland, Texas 79705 (915) 686-8235
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit I, 1980' FSL and 660' FEL, Section 31, T18S, R33E
6. If Indian, Allottee or Tribe Name
7. If Unit or CA, Agreement Designation
8. Well Name and No.
Gazelle 31 Federal #3
9. API Well No.
30-025-35339
10. Field and Pool, or Exploratory Area
Corbin Morrow, South
11. County or Parish, State
Lea County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Surface Casing and Cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

01/18/01: MIRU Patterson #45 and sped well at 0600 hrs on 01/19/01.

12/10/00: Drilled to 439'. C&C hole. RU and ran 10 jts of 13-3/8", 48#, H40, ST&C casing to 439'. Cement casing using 200 sx 35/65 "C" poz and 200 sx "C" 2% CC. Circ 89 sx cmt to surface. WOC 19 hrs. Cut off csg and weld on wellhead. NU BOPE and test.

14. I hereby certify that the foregoing is true and correct

Signed

Title Regulatory Analyst

Date 01/26/01

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

PETROLEUM ENGINEER

Date

(ORIG. SGD.) GARY GOURLEY

RECEIVED

JAN 29 '01

U.S.
ROSWELL, NM