

WBSA # 249

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

T. Anhy	1463	T. Canyon
T. Salt	1588	T. Strawn
B. Salt	2671	T. Atoka
T. Yates	2765	T. Miss
T. 7 Rivers	3112	T. Devonian
T. Queen	3667	T. Silurian
T. Grayburg	3985	T. Montoya
T. San Andres	4288	T. Simpson
T. Glorieta		T. McKee
T. Paddock		T. Ellenburger
T. Blinberry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkard		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

### Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

## OIL OR GAS SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
1463	1588	125	ANHYDRITE				
1588	2671	1083	SALT				
2671	2765	94	ANHYDRITE/DOLOMITE				
2765	3112	347	SAND/DOLOMITE/ANHYDRITE				
3112	3667	555	DOLOMITE/ANHYDRITE				
3667	3985	318	SAND/ANHYDRITE				
3985	4288	303	DOLOMITE				
4288	4800TD	512	DOLOMITE				