

DRILLING PROGRAM

Lynx Petroleum Consultants, Inc.
Hawkeye 7 Federal No. 2
1650' FSL & 1980' FEL
Section 7, T-19S, R-32E
Lea County, NM

The following items supplement Form 3160-3 in accordance with instructions contained in Onshore Oil and Gas Orders #1 and #2, and all other applicable federal and state regulations.

1. SURFACE FORMATION : Sandy Soil of Quaternary Age

2. ESTIMATED TOPS OF GEOLOGICAL MARKERS :

Yates	-	2825'
Delaware	-	5175'
Bone Spring	-	6900'
Wolfcamp	-	10320'
Strawn	-	11115'
Atoka	-	11440'
Morrow	-	11775'

ESTIMATED DEPTHS TO WATER, OIL, OR GAS FORMATIONS :

Fresh Water	-	Above 200'
*Oil, Gas, and Water	-	Delaware, Bone Spring, Morrow

* Productive horizons to be protected by 5 1/2" casing and cement

4. PROPOSED CASING PROGRAM :

20"	0' -	40'	0.30 wall thickness
13 3/8"	0' -	850'	48.0# J-55 STC
8 5/8"	0' -	4500'	32.0# J-55 Buttruss
5 1/2"	0' -	1400'	17.0# P-110 LTC
5 1/2"	1400' -	10800'	17.0# N-80 LTC
5 1/2"	10800' -	12650'	17.0# P-110 LTC