

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resou.

Form C-101
Revised March 17, 1999

Oil Conservation Division
2040 South Pacheco
Santa Fe, NM 87505

Submit to appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address RICKS EXPLORATION, INC. 210 PARK AVE OKLAHOMA CITY, OKLAHOMA 73102		LYNN SUCHY 405-516-1130	OGRID Number 168489
Property Code 28798		STATE VII	API Number 30-025-35678
Well No. 7			

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A/1	1	17S	34E		660'	NORTH	660'	EAST	LEA

Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

Proposed Pool 1 VACUUM-ATOKA, MORROW NORTH (86800)	Proposed Pool 2
---	-----------------

Work Type Code N	Well Type Code G	Cable/Rotary ROTARY	Lease Type Code PS	Ground Level Elevation 4033'
Multiple NO	Proposed Depth 13,000'	Formation Atoka - Morrow	Contractor PATTERSON	Spud Date WHEN APPROVED

Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
25"	20"	Conductor	40'	Redi-mix	surface
14 3/4"	11 3/4"	42	1600'	780 Sx	surface
12 1/4"	8 5/8"	24	5000'	1190 Sx.	1100' FS
7 7/8"	5 1/2"	17	13,000'	670	7500' FS

Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone.

Describe the blowout prevention program, if any. Use additional sheets if necessary.

1. Drill 25" hole to 40'. Set 40' of 20" conductor and cement to surface with Redi-mix.
2. Drill 14 3/4" hole to 1600'. Run and set 1600' of 11 3/4" J-55 42# ST&C casing. Cement with 1190 Sx. of Class "C" cement + 2% CaCl + 1/4# Flocele/Sx. circulate cement to surface.
3. Drill 12 1/4" hole to 5000'. Run and set 5000' of 8 5/8" 24&32# J-55 ST&C casing. Cement with 1190 Sx. of Class "C" cement + 2% CaCl + 1/4# Flocele/Sx. estimate top of cement 1100'.
4. Drill 7 7/8" hole to 13,000'. Run and set 13,000' of 5 1/2" 17# N-80 LT&C casing. Cement with 670 Sx. of Class "H" Premium Plus cement + additives. Top of cement at least 500' above upper most Perforation.

Permit Expires 1 Year From Approval
Date Unless Drilling Underway

I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

Title:

Date:

Joe T. Janica

Agent

08/28/01

Phone:

505-391-8503

OIL CONSERVATION DIVISION

Approved by:

Title:

Approval Date:

Expiration Date:

Conditions of Approval: