

Submit 3 copies to Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-35748
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator KUKUI Operating Company		6. State Oil & Gas Lease No.
3. Address of Operator 203 W. Wall Street, Suite 810 Midland, TX 79701		7. Lease Name or Unit Agreement Name: North Lusk 32 State
4. Well Location Unit Letter L ; 1980 feet from the South line and 660 feet from the West line Section 32 Township 18S Range 32E NMPM County Lea		8. Well No. 1
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3691' GR		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/02/01 Noon - 12/04/01: Drill 17" hole to 575'.

12/4/01: Ran 14 jts 13-3/8", 48.0 lbs./ft., H-40, STC surface casing to 573'. Cement with 285 sacks Class "C" light and 200 sacks Class "C" +2% CaCl₂. Circulated 37 sacks cement to reserve pit. WOC. Weld on 13-5/8" head. Test ok to 600 PSI.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

L. K. Strider

TITLE

Western District Manager

DATE 01/08/02

Type or print name

Larry K. Strider

Telephone No. 915-687-6200

(This space for State use)

APPROVED BY

Conditions of approval, if any:

TITLE

ORIGINAL SIGNED BY

P. L. F. KAUTZ

PETROLEUM ENGINEER

DATE

JAN 10 2002