

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____

The summary on this page is for the condition of the well at above date.

Commenced drilling November 15, 1956 Finished drilling January 15, 1957

(Denote gas by G)

No. 1, from	3970	to	3994	Dry	No. 4, from		to	
No. 2, from	4584	to	4612	Dry	No. 5, from		to	
No. 3, from		to			No. 6, from		to	

No. 1, from 550 to 595 No. 3, from _____ to _____
No. 2, from 705 to 730 No. 4, from _____ to _____

[illegible][illegible]

Heaving plug—Material Length Depth set

Adapters—Material..... Size

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet
Cable tools were used from 0 feet to 4657 feet, and from _____ feet to _____ feet

Put to producing	19
------------------	----

The production for the first 24 hours was barrels of fluid of which% was oil;% emulsion;% water; and% sediment. Gravity: 36.

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

_____, Driller _____, Driller
_____, Driller _____, Driller

FROM—	TO—	TOTAL FEET	FORMATION
0	50	50	Sand
50	60	10	Caliche
60	550	490	Red bed
550	595	45	Sand
595	630	35	Shale
630	635	5	Sand
635	640	5	Red bed
640	645	5	Sand
645	670	25	Red bed
670	705	35	Sandy Shale
705	730	25	Sand
730	1060	330	Red bed
060	1230	170	Anhydrite
230	1400	170	Salt
400	1430	30	Anhydrite
430	1515	85	Salt
515	1525	10	Anhydrite
525	2165	645	Salt
165	2190	25	Gyp
190	2195	5	Anhydrite
195	2350	155	Salt
350	2660	310	Anhydrite
660	2695	35	Red Shale
695	2870	185	Anhydrite

FROM--	TO--	TOTAL FEET	FORMATION
2870	2890	20	Pink Lime
2890	2967	77	Anhydrite
2967	2980	13	Gray Lime
2980	3590	610	Anhydrite
3590	3604	14	Brown Lime
3604	3661	57	Anhydrite
3661	3673	12	Lime
3673	3970	297	Anhydrite
3970	3994	24	Sand (Red)
3994	4300	306	Sandy Lime
4300	4470	170	Lime
4470	4482	12	Sand
4482	4584	102	Lime
4584	4612	28	Sand
4612	4658	46	Sandy Lime

T.D.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

4½" casing was set to total depth of 4658'. casing was perforated 4586' to 4610' well was treated with sand-fractor and made salt water. Swabbed with casing swap 18 bbl./hr. unable to swap fluid lower than 2500'.

HISTORY OF OIL OR GAS WELL

16-43084-2 U. S. GOVERNMENT PRINTING OFFICE