

12 210	244					5 sacks aqua gel
10 3/4	1083					12 sacks aqua gel
8 5/8	2533	30	Denton	9.4	7	" " "

Heaving plug—Material Cement Length 60 feet Depth set 2490 - 2550
 Adapters—Material Size 40 feet 1115 - 1155

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth set	Depth cleaned out

TOOLS USED

Rotary tools were used from 4730 feet to 6200 feet, and from feet to feet
 Cable tools were used from 0 feet to 4730 feet, and from feet to feet

DATES

July 16, 1951, 19

The production for the first 24 hours was barrels of fluid of which % was oil; %
 emulsion; % water; and % sediment.

If gas well, cu. ft. per 24 hours

Rock pressure, lbs. per sq. in.

EMPLOYEES

J. D. Smith Driller
 V. Smith Driller
 C. Dawitt Driller

FORMATION RECORD

FROM-	TO-	TOTAL FEET	FORMATION
0	320	320	Red Bed
320	340	20	Water Sand
340	410	70	Red Bed
410	415	5	Water Sand
415	460	45	Sandy Red Bed
460	530	70	Water Sand
530	580	50	Sandy Red Bed
580	600	20	Red Bed
600	620	20	Hard Sand
620	745	125	Red Bed and Red Rock
745	755	10	Sand
755	1083	328	Red Bed and Red Rock
1083	1220	137	Anhydrite
1220	1240	20	Salt
1240	1310	70	Anhydrite and Salt
1310	2471	1161	Salt
2471	2750	279	Anhydrite
2750	2800	50	Anhydrite and red Shale
2800	3000	200	Anhydrite
3000	3040	40	Anhydrite sandy
3040	3155	115	Anhydrite
3155	3261	106	Anhydrite and lime
3261	3267	6	Gas Sand
3267	3285	18	Lime