

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons.
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Manzano Oil Corporation

3. Address and Telephone No.

P.O. Box 2107, Roswell, NM 88202-2107 (505) 623-1996

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FSL & 660' FWL
Sec 14, T19S, R33E

5. Lease Designation and Serial No.

NM-56749

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. **Jones #1**
Federal USA L #9

9. API Well No.

30-025-01666

10. Field and Pool, or Exploratory Area

Tonto Seven Rivers

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/05/98 Received plugging orders from Joe Lara w/BLM on 2/03/98 to plug as follows:
100' cement plug 50' in 8-5/8" csg stub @ 460' & 50' outside of stub. A 50' surface plug.

RIH w/open ended tbq. Tag @ 490'. Attempted to work down to 520'. Would not go. Pumped a 60 sx Class "C" cmt plug w/3# CaCl2. Wait 2 hrs. Tagged plug @ 340'. Pumped a 50 sx Class "C" cmt plug. Brought circulated cement to surface. All plugs were set in place w/9.5 mud laden fluid. Plugging witnessed by Steve Caffey w/BLM.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Allen J. Hernandez Title Engineering Technician

(This space for Federal or State office use)

Approved by ORIG. SGD.) DAVID R. GLASS

Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date 2/6/98

Date FEB 18 1998