

APPROVED
JUL 11 1962
RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Alamos
Lease No. LC-070023
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
JUL 10 1962
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO.

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHOT
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL <input checked="" type="checkbox"/>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

ARTESIA, OFFICE

July 9, 1962

Well No. 1 is located 300 ft. from IN line and 660 ft. from W line of sec. 14
35N (1/4 Sec. and Sec. No.) 19N (Twp.) 33E (Range) 107W (Meridian)
Tonto (Field) Los Alamos (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3634 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to a T.D. of 5013' and temporarily abandoned 2/4/54 after plugging back to 4400' in 6-1/4" hole with 30 sack plugs at bottom of hole and at 4400'. As per phone conversation with Mr. Knauf as of date, preparations are being made to Plug and abandon this well with the following requirements to be met.

- Set 35 Sack Cement Plug at 4100' above base of formation
- Set 35 Sack Cement Plug at 3070' at base of salt section
- Set 35 Sack Cement Plug at 1500' Above salt section. (Top of salt 1575')
- Pull and recover as much 8-5/8" casing as possible.
- Set 20 Sack Cement Plug at surface and erect regulation Marker filled with concrete.
- Good quality gel mud to be used as plugging mud.
- Location cleaned for final abandonment.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Hondo Drilling Company, Inc.
Address P.O. Drawer 63.
Artesia, N.M.

By T.J. Sivley
T.J. Sivley, F.P.
Title Owner-Operator.