

(SUBMIT IN TRIPLICATE)


UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Las Cruces**

029448

Lease No.

Unit



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, November 20, 1944

William Bobb

Well No. **1** is located **660** ft. from **S** line and **660** ft. from **E** line of sec. **17**

SE 1/4 Sec. 17
(1/4 Sec. and Sec. No.)

19-S
(Twp.)

33-E
(Range)

N. M. P. M.
(Meridian)

Wilcoat
(Field)

Lea

(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **3639** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total Depth, 4295' - Lime.

13-3/8" casing cemented at 310' with 100 sacks; 8-5/8" cemented at 1402' with 100 sacks; 7" mudded at 3934'.

This well has been drilled to 4295' without encountering oil or gas production. Water was encountered at 3615' to 3625' and the 7" casing was run through this section so that the well could be carried to the Artesia Red Sand. Water was encountered in the Artesia Red Sand from 4235' to 4265'. We therefore desire to plug and abandon this well as follows:

(See attached sheet)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **THE TEXAS COMPANY**

Address **Box 1270**

Midland, Texas

By

Title **Drlg. & Prod. Foreman**

WILLIAM BOBB WELL NO. 1

Plug the bottom of the hole with 40 sacks of cement from 4295' to approximately 4080' and fill the hole with heavy mud. After pulling all possible 7" casing, cement plugs will be spotted as follows: 30 sacks, 3645-3545'; 20 sacks, 2987-2920' (base of the salt); 20 sacks at the top of the salt and in the bottom of the 8-5/8" casing, from 1449' to 1382'. Part and pull approximately 1100' of the 8-5/8" casing. Spot cement plugs as follows to protect water sand (685'-810'): 20 sacks, 838-810'; and 20 sacks, 685-657'. Cement customary 4" pipe marker in the top of the hole with 20 sacks. All mud and cement will be pumped in through tubing.

The above confirms telephone conversation and approval of your office on November 18, 1944.

CONFIDENTIAL

On 1998, the FBI received information from a confidential source that a person, identified as [REDACTED], was involved in a series of activities that could be related to the [REDACTED] case. The source provided information that [REDACTED] was in contact with [REDACTED] and [REDACTED] in the [REDACTED] area. The source also mentioned that [REDACTED] was involved in a [REDACTED] operation. The FBI is currently conducting an investigation into this matter and is seeking additional information from the public. If anyone has information regarding this case, please contact the FBI at [REDACTED] or call the tip line at [REDACTED].