(Feb. 1951)								
								
	*							

N. M. O. O. O. GOPY.
(SUBMIT IN TRIPLICATE)

Land Office 188 Crucas

Lease No. 064780

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY も (の) 11 う

1960 SLINDRY NOTICES AND DEPORTS

NOTICE OF I	NTENTION TO DRILL		SUBSEQUENT REPORT	OF WATER SHUT-OFF	
	NTENTION TO CHANGE PLANS		11	OF SHOOTING OR ACIDIZING	
NOTICE OF I	NTENTION TO TEST WATER SHUT-OFF	· 		OF ALTERING CASING	
NOTICE OF I	NTENTION TO RE-DRILL OR REPAIR WELL			OF RE-DRILLING OR REPAIR	
NOTICE OF I	NTENTION TO SHOOT OR ACIDIZE			OF ABANDONMENT.	
NOTICE OF I	NTENTION TO PULL OR ALIER CASING			L HISTORY	
NOTICE OF I	NTENTION TO ABANDON WELL				
	(INDICATE ABOVE BY CHECK	MARK NAT	URE OF REPORT, NOTICE	E, OR OTHER DATA)	
	Madamal 16		Sep	tember 23,	, 19.60.
'ell No	Pederal 18 is located 2310 ft. f	rom {	$\left\{\begin{array}{c} \mathbf{N} \\ \mathbf{S} \end{array}\right\}$ line and $\left[\begin{array}{c} 33 \\ 34 \end{array}\right]$	\mathfrak{g}_{-} ft. from $\{W\}$ line of sec.	18
	U/4 Sac. 18 19-8 : and Sec. No.) (Twp.)	(Ran	3-B (M	eridian)	
West T	bato (Y-SR) Los (Cor	inty or Sub	odivision)	State or Territory)	
نادينوام مر	on of the derrick floor above sea		. 6		e de maria promi No de desta la
ie elevati					Section Street
ste names of			OF WORK		
	with avhacted debrus to oplective sauds: suo				
				roposed casings; indicate mudding job rk)	MEXICO
spth of sek to t	It is proposed to drill 3300 feet. Approximatel the surface. Production atted back to the anhydrite by perforating 3-1/2° co	this y 250 string	well with rot feet of 8-5/6 s will be 5-1/2 to the selt se	cary tools to an appro	MEXIC Eximate ated ettou
spth of sek to t	It is proposed to drill 3300 feet. Approximatel the surface. Production ated back to the anhydrit	this y 250 string	well with rot feet of 8-5/6 s will be 5-1/2 to the selt se	cary tools to an appropriate to an appropriate casing will be come of the case	MEXICO Eximate Sted Ittom
spth of sek to t	It is proposed to drill 3300 feet. Approximatel the surface. Production ated back to the anhydrit	this y 250 string	well with rot feet of 8-5/6 s will be 5-1/2 to the selt se	ARRIVA GEN cary tools to an appropriate to appropriate to appropriate to appropriate to appropriate t	MEXIO eximate ated ettom
epth of sek to t ad comm smpletes	It is proposed to drill 3300 feet. Approximatel the surface. Production at the subject to the anhydrit by perforating 5-1/2° c	this y 250 string a abov asing.	well with roof feet of 8-5/6 will be 5-1/m the sait se	PECHIVEI SET 200 U.S. L. 200 ANTENA, NEW	MEXICO Palmate Rted Rton
epth of sek to t ad comm smpletes	It is proposed to drill 3300 feet. Approximatel the surface. Production ated back to the anhydrit	this y 250 string a abov asing.	well with roof feet of 8-5/6 will be 5-1/m the sait se	PECHIVEI SET 200 U.S. L. 200 ANTENA, NEW	MEXICO Palmate Rted Rton
epth of sek to t ad comm smpletes	It is proposed to drill 3300 feet. Approximatel the surface. Production at the subject to the anhydrit by perforating 5-1/2° c	this y 250 etring s abov asing.	well with rot feet of 8-5/6 ; will be 5-1, we the selt se	PECHIVEI SET 200 U.S. L. 200 ANTENA, NEW	MEXICO Palmate Rted Rton
epth of sck to t ad comm smpleted	It is proposed to drill 3300 feet. Approximatel the surface. Production ated back to the anhydrit i by perforating 5-1/2° co that this plan of work must receive approve	this y 250 etring s abov asing.	well with rot feet of 8-5/6 ; will be 5-1, we the selt se	PECHIVEI SET 200 U.S. L. 200 ANTENA, NEW	MEXICO winate mted cton