

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐2. NAME OF OPERATOR
Amoco Production Company3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 690' FWL, Sec. 18
AT TOP PROD. INTERVAL: (Unit E, SW/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

5. LEASE

LC-064790

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal AC

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Buffalo Penn Gas Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18-19-33

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3635' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 2-13-81. Set cast iron bridge plug at 12015' and capped with 30' cement. Ran pipe recovery log from 7000'-11000'. Perforate at 7120' with 4 JSPF and 11610' with 4 JSPF. Circulated hole with 400 bbl. w. Set a cement retainer at 10307'. Pumped 850 SX Class H cement and could not pull out of retainer. Cut tubing at 3710'. Drill from 3750'-3850'. Run chemical cutter and cut tubing at 3866'. Pull tubing and stuck at 3868'. Well currently shut-in until further evaluation.

0+4-USGS, H 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Gerald L. Foster TITLE Admin. Analyst DATE 4-16-81APPROVED BY PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

APR 22 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

737 (Weld)