


N. M. O. C. C. COPY

Form 9-331a
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

HOBBS OFFICE O. C. C.
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. NM-02796
Unit P

APPROVED
NOV 6 1963

E. G. HUBBLE
ACTING DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 9, 1963, 19

Well No. 2 is located 1220 ft. from N line and 660 ft. from E line of sec. 22

SE/4 22
(1/4 Sec. and Sec. No.)

19S 33E
(Twp.) (Range)

WPM
(Meridian)

Tonto
(Field)

Lea County
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

In agreement with our Notice of Intention to Abandon Well of August 5, 1963 and verbal conversation with Mr. Knauf on August 6, 1963, this well has now been plugged as per follows, and witnessed by Mr. Knauf up through Shot off point in Casing.

After establishing circulated Top of cement around 5-1/2" Production string to be 1350' from surface by free point, 50 Sacks of Neat Cement with 12 1/2 Lbs of Gilonite per sack was squeezed into formation at 2800 Libs without further movement and followed with 50 sacks of Neat cement and then 120 sacks of 50/50 Pozmix cement with 10% Gel. Top of Solid cement in 5-1/2" Casing came back to 868' - Pressure applied through out - 2800 PSI. 5-1/2" Casing was shot off at 820' and pulled after spotting 20 sack net cement plug from 820' - 740' calculated to be in 7-7/8" Hole.

20 Sack Plug set in 8-5/8" Casing at surface with regulation marker erected. Final abandonment report to follow pending lease clean-up.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company T.J. Divilley & Mondo Drilling Company

Address P.O. Drawer 66
Artesia, New Mexico

By T.J. Divilley
Title Operator