


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 029446

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON <u>Water Well</u> <u>x</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, August 2, 1945

W. H. Baskin
Well No. 2 is located 1980 ft. from S line and 1980 ft. from E line of sec. 22
NW 1/4 Sec. 22 19-S 33-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Tonto Lea New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3635 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Our "Subsequent Report of Abandonment" of this well and its re-completion as a water well was approved by your office under date of March 22, 1945. Since we no longer have any need for this water well, we now desire to plug and abandon it, salvaging as much of the 8-5/8" casing as possible. In order to complete as a water well, the lower portion of the hole was plugged and a cement plug spotted in the bottom of the 8-5/8" casing before it was perforated from 810' to 700' with 220 holes, as previously reported. We propose to part and pull all possible (approximately 1000') of 8-5/8" casing and spot cement plugs as follows to protect the water sand: 20 sacks, 838'-810'; and 20 sacks, 700'-672', setting the customary 4" pipe marker in the top of the hole with 20 sacks. The hole will be filled with heavy mud before spotting cement plugs, and all mud and cement will be pumped in through tubing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE TEXAS COMPANYAddress Box 1270Midland, TexasBy L. F. ShupatTitle District Superintendent

THE HISTORY OF THE

REIGN OF
HAROLD GODWINSON
BY
JOHN RUSKIN

LONDON: 1871

PRINTED BY
JOHN WATKINS, 10, ST. MARTIN'S LANE

AND
SOLD BY
ALL BOOKSELLERS

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE

AND
BY THE
AUTHOR, 10, ST. MARTIN'S LANE