

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 029449
Unit HOODS OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....		SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, November 17, 1944

Fred Cole

Well No. 2 is located 660 ft. from N line and 660 ft. from E line of sec. 27

NE1 NE1, Sec. 27 19-3 33-E N. H. I. M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Tonto

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3612 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Our Notice of Intention to Change Plans and complete this well as a water well was approved by your office 8-26-44. It would be to our advantage to complete our Baskin #2 as a water well, and plug and abandon this well, which we propose to do in the following manner.

Having set a cement plug in bottom of 8-5/8" casing and plugged bottom of hole, the 8-5/8" casing will be parted and pulled at approximately 1100'. Cement plugs spotted as follows to protect the water sand from 690' to 760': 20 sacks, 788'-760'; 20 sacks, 690'-662'. Pull all possible 10-3/4" casing and cement customary 4" pipe marker in top of hole with 20 sacks. The hole will be filled with heavy mud before spotting above cement plug, and all mud and cement will be pumped in through tubing. Above confirms telephone conversation and approval of your office 11-16-44.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE TEXAS COMPANY

Address Box 1270

Midland

By W. R. Baskin

Title Dir. & Prod. Foreman