

FORMATION RECORD—Continued

FROM—	TO—	TOTAL FEET	FORMATION
NOTE: Top Yates—3015'			
Top Seven Rivers—3237'			
Cement Plug from 3215-3280 (20 Sacks cement)			
Cement Plug from 2858-2908 (20 Sacks cement)			
Cement Plug from 1723-1773 (20 Sacks cement)			
15 sacks in top of 10-3/4" casing, rest of hole left full of			
low water loss mud. Plate welded across top of 10-3/4" Collar and			
4" marker welded to plate.			
DST 3259-3280			
5/8 Choke bottom, 1" choke top tool open 40 minutes until dead.			
Recovered 30' muddy salt water, 2470' salty sulphur water.			
I. F. —400#, F. F. —1185#,			
15 minutes shut-in—1185#			

HISTORY OF OIL OR GAS WELL

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

DATE OF COMPLETION _____

NAME OF WELL _____

LOCATION _____

DETAILED HISTORY OF THE WELL (See instructions above)

DATE OF REPORT _____

REPORTED BY _____

REVIEWED BY _____

APPROVED BY _____

FOR OFFICIAL USE ONLY

U. S. GOVERNMENT PRINTING OFFICE