



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Las CrucesLease No. 063591Unit Federal-Carder

## SUNDRY NOTICES AND REPORTS ON WELLS

|  |   |
|--|---|
| NOTICE OF INTENTION TO DRILL.....  | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |
| NOTICE OF INTENTION TO CHANGE PLANS.....                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....                              | SUBSEQUENT REPORT OF ALTERING CASING.....       |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....                          | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....                                 | SUBSEQUENT REPORT OF ABANDONMENT.....           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....                             | SUPPLEMENTARY WELL HISTORY.....                 |
| NOTICE OF INTENTION TO ABANDON WELL..... <input checked="" type="checkbox"/> |   |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico, March 28, 1956Well No. 2 is located 1980 ft. from AN line and 660 ft. from E line of sec. 29 30NESE30

(1/4 Sec. and Sec. No.)

19S

(Twp.)

33E

(Range)

NMPM

(Meridian)

Glen Yates- Ext.

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 5600' - Delaware Sand- Dry- no oil or water- To Plug & Abandon  
DST - from 2993- 3033- Dry- no oil or water-  
DST - from 3193- 3250- Recovered water- no oil  
DST - from 5330- 5360- Dry- no oil or water-  
3/28/56- Filled hole w/ heavy mud and spotted 25 Sks. Cement plug in bottom- to 5519'  
25 Sack cement plug from 4669 to 4750  
25 sack cement plug from 3119 to 3200 Top Yates  
25 sack cement plug from 2694 to 2775 Base Salt  
25 sack cement plug from 1269 to 1350 Top Salt  
25 sack cement plug from 223 to 304 Base surface casing  
25 sack cement plug in top of surface pipe & base of cellar with 4"  
Regulation Marker 4' above surface level.

Per verbal phone approval as of this date from Mr. Frost's office.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Sinclair Oil & Gas CompanyAddress 520 E. Broadway, Hobbs, N.M.By [Signature]Title Dist. Supt.

Orig. &amp; 4cc- USGS

1cc- FHR-JTR-f