

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-105
Effective 1-1-65

SUNDRY NOTICES AND REPORTS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR REWORK WELLS. USE APPLICATION FOR PERMIT TO DRILL OR REWORK WELLS.

1. OIL WELL ☐ GAS WELL ☐ OTHER- WIW
2. Name of Operator Mobil Oil Corporation
3. Address of Operator Box 633, Midland, Texas 79701
4. Location of Well UNIT LETTER E 660 FEET FROM THE West 1980 FEET FROM THE North LINE, SECTION 24 TOWNSHIP 17-S RANGE 34-E NMPM. 15. Existing (Show 4029-GR

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. B-1520
7. Unit Agreement Name
8. Form or Lease Name Bridges State
9. Well No. 20
10. Field and Pool, or Wildcat Vac - G - SA
12. County Lea

16. Check Appropriate Box To Indicate NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	16. Check Appropriate Box To Indicate NOTICE OF INTENTION TO: PUMP AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐
--	--

16. Check Appropriate Box To Indicate SUBSEQUENT REPORT OF: REMEDIAL WORK ☒ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐	16. Check Appropriate Box To Indicate SUBSEQUENT REPORT OF: ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER ☐
--	---

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

BRIDGES STATE #20, Vac Graburg SA Field, Lea County, New Mexico, OBJECTIVE:
Set a liner, perf, and acidize to improve the injection profile. 4690 TD.

Ran 17 jts 5" 15# J55 ST&C liner on BWS Type C hanger w/CRL pkr on 2-7/8 tbg to 4680, T/liner @ 4144, Howco cmtd w/400x Class C Neat 0.3% CFR2 & 1/8# Flocele/x, set pkr, rev out no cmt, press T/liner 800, bled off to 400#/held ok, POH

Dresser-Atlas ran BHC-N-Collar-Corr log from 3150-4668, then perf 5" liner in the SA @ 4536-68; 4573-76; 4580-82; & 4591-4598 w/ 1 JSPF, total 51 holes

Ran Baker 5" Model R pkr set @ 4221, Runco treated SA perfs 4536-4598 w/ 800 gals Xylene + 200 gals 15% NEA + 2 gals Adafoam, TTP 0-1600, AIR 3.8 BPM, ISIP 1000

Runco acidized perfs w/2500 gals 15% iron stabilized acid used 75 RCNBS flushed w/7500 gals TFW, TTP 2300-1700, AIR 5.0 BPM, ISIP 1300, 10 min 1000, Ran Baker 7" tension pkr on 132 jts 2-7/8 CL tbg, loaded hole w/TFW, set pkr @ 4090 w/9000# T, inst'l inj head,

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine O. Tucker

Proration Clerk

DATE **12/7/73**

Orig. Signed by
Joe D. Ramsey
DATE 12/7/73