

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

November 28, 1962

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Socony Mobil Oil Company, Inc.**

**State Bridges**

Well No. **22**

in **N**

(Unit)

**SE**

**SW**

(Company or Operator)

**24**

T. **17S**

R. **34E**

NMPM,

**Vacuum**

Pool

**1/4**  
(40-acre Subdivision)

**1/4** of Sec.

**Lea**

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 4700'

Csg: 10 3/4" @ 828' w/220 sx., 7" @ 4278' w/220 sx.

Perfs: Open Hole 4278-4700

Propose to clean out & cement open hole w/approx. 350 sx Incor neat cement. Pressure test 7" csg. w/1200# and repair if necessary. Drill 6 1/2" hole to 6850' w/fresh water. Run Gamma Ray surface to TD. Run GR-Sonic & IBS surveys 4278' to TD. Set 1000' of 17# flush joint 5 1/2" plus 1850' of 15# J-55 5" liner 4000' to 6850'. Cement liner w/400 sx Incor 4% Gel tailed in w/75 sx Incor Neat cement. Circ. cement behind liner. Test top of liner w/1200# for 15 mins. Run GR collar log top of liner to TD & perforate lower San Andres and Paddock formations at intervals indicated by surveys. Test and attempt completion in both formations.

Approved....., 19.....  
Except as follows:

Approved.....  
OIL CONSERVATION COMMISSION

By.....

Title.....

**Socony Mobil Oil Company, Inc.**

Company or Operator

By.....

Position.....

**Group Supervisor**

Send Communications regarding well to:

Name..... **Socony Mobil Oil Company, Inc.**

Address..... **Box 2406, Hobbs, New Mexico**