

BRIDGES STATE
WELL # 32 WIW
VACUUM GRAYBURG (SAN ANDRES) FIELD
LEA COUNTY, NEW MEXICO
PROPOSED COMPLETION

C, 25, T 17-S, R 34-E, 660' FNL, 1980' FWL

KB = 4013'

GL = 4002'

15 SX CLASS C NEAT CMT PLUG
FROM SURFACE-30'

10-3/4" 35.75# L.W. CSG @ 815'
CMT'D W / 257 SX CIRC.

70 SX CLASS C NEAT CMT PLUG FROM +900-765' ACROSS
7" CSG STUB @ +850 & 10-3/4" CSG SHOE @ 815'
PLUG MUST BE TAGGED!

50 SX CLASS C NEAT CMT PLUG FROM 1770-1670'
PERFED & SQZ'D ACROSS SALT TOP @ 1720'
PLUG MUST BE TAGGED!

TOC @ 2735' (CALCULATED)

40 SX CLASS C NEAT CMT PLUG FROM 2895-2685'
ACROSS SALT BASE @ 2845' AND TOC @ 2735'

TOL @ 4045'

TOC @ 4065' (TS)

7" 24# SL CSG @ 4210'
CMT'D W / 217 SX

CIBP @ 4450' W/ 40 SX CLASS C NEAT CMT CAP FROM
4500-3995' ACROSS 7" CSG SHOE @ 4210' & 4-1/2" TOL @ 4045'

5580'

SAN ANDRES PERFS 4481-4843'

GLORIETA PERFS 5975-6000' (SQZ'D W/ 100 SX)

6580'
6600'

4-1/2" BAKER CIBP @ 6600' W/ 20' CMT CAP

BLINEBRY PERFS 6663-6712'

4-1/2" 9.5# J-55 LINER 4045-6800' CMT'D W / 400 SX

PBTD=5580'

TD=6800'

BS32P.PRE

ALS 09/27/93

RECEIVED

OLD HOUSE
OFFICE