

FORM

ILLEGIBLE

FORM 100-1000


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Texas Company

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate reasonable data by following it with (1). SUBMIT IN TRIPLICATE.

DUPLICATE

Drawer "K", Pink, Texas

State of New Mexico

Company or Operator

Well No.

of Sec.

Lease

Section

Field

County

R. 34-2

N. M. P. M.

Well is

feet south of the North line and

feet west of the East line of

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Address

Box 2332, Houston, Texas

Drilling commenced

Drilling was completed

Name of drilling contractor

Address

Elevation above sea level

feet

aterrick floor

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

No. 1, from

to

No. 4, from

to

No. 2, from

to

No. 5, from

to

No. 3, from

to

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
30 5/8"	22.75	8	LU	200'	TEXAS PATTERNS				
7 5/8"	20.40	8	SALE	1331'	SALES GUIDE				
8 1/2"	17	10	"	4120'	HALLIBURTON GUIDE				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10 5/8"	200'		200	Halliburton		
7 5/8"	1331'		200	"		
8 1/2"	4120'		200	"		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4730 feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing June 30, 1930, 100 barrels of fluid of which 100% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, Be 20
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____ Gas-oil Ratio - 300'

EMPLOYEES

John Martin, Driller D. L. Rogers, Driller
O. D. White, Driller _____, Driller _____

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 19th day of July, 1930, at Pink, Texas, Date
Name _____ Position District Superintendent
Representing The Texas Company
Company or Operator
Drawer "K", Pink, Texas
Address _____
My Commission expires 8-31-30

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
128	128	128	Caliche
115	115	115	Caliche & Sand
873	873	873	Red Rock & Red Beds
808	808	808	Red Beds & Shells
340	340	340	Red Rock & Red Beds
411	411	411	Red Beds & Shells
80	80	80	Anhydrite
242	242	242	Anhydrite, Red Beds and Salt
514	514	514	Salt & Anhydrite
98	98	98	Anhydrite, Gypsum, and Gyp
82	82	82	Anhydrite & Gyp
44	44	44	Sand & Anhydrite
176	176	176	Anhydrite
104	104	104	Brown Lime & Anhydrite
494	494	494	Anhydrite & Gyp
46	46	46	Anhydrite
332	332	332	Anhydrite & Gyp
73	73	73	Gray Lime & some Anhydrite
473	473	473	Gray & Brown Lime
72	72	72	Saturated Lime
20	20	20	Medium Lime

Total Depth 4730'

Deviation tests as follows:

400' - 0°	2800' - 0°
1000' - 0°	3000' - 3/4°
1500' - 1/2°	3500' - 1°
2000' - 1°	4000' - 1/2°