

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified ~~on~~ begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Midland, Texas

March 10, 1948

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the The Texas Company's
State of New Mexico "T" Well No. 1 in SE-NE-1
Company or Operator Lease
of Sec. 25, T. 17-S, R. 34-E, N. M. P. M., Vacuum Field.
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

TD: 4753 - Lime

As reported on our Form C-103 dated January 9, 1948, attempts to make this well a commercial producer proved unsuccessful. We therefore propose to abandon, salvage & plug this well as follows:

Ground Elevation Measurements

7-5/8" casing set at 1586' and cemented with 300 sacks.
5-1/2" casing set at 4091' and cemented with 200 sacks.

Hole is to be filled with mud through tubing, spot 10 sacks cement plug from 4753-4653', 15 sacks cement plug from 4050-4125' (bottom of 5 1/2" casing). Part and pull all possible 5 1/2" casing (possible recovery - 1800'). Spot 20 sacks cement plug from approximately 50' down in parted 5 1/2" casing to 50' above top of 5 1/2" casing. Spot 25 sacks cement plug from 1550-1650' (bottom of 7-5/8" casing) and 25 sacks cement plug from 100-0'. (See Over)

Approved _____, 19____
except as follows: _____

THE TEXAS COMPANY

Company or Operator

By _____

Position District Superintendent
Send communications regarding well to

Name The Texas CompanyAddress Box 1270Midland, Texas

OIL CONSERVATION COMMISSION,

By _____

Title _____

Cement used 4" x 10' pipe marker 4' above ground level in top of hole.

All 7-5/8" casing to be left in hole.
All cement to be spotted through tubing.