

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	X
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	X
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

November 6, 1962

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Soceny Mobil Oil Company, Inc.

(Company or Operator)

State Bridges

Lease

Well No. 30

in G

(Unit)

SW

1/4

NE

1/4 of Sec.

26

T.

17S

R.

34E

NMPM.

Vacuum

Pool

(40-acre Subdivision)

Lee

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 4740'

Csg: 10 3/4" @ 820' w/300 sz., 7" @ 4250' w/210 sz.

Perfs: Open hole 4250-4740

Propose to clean out and cement open hole with approx. 350 sz Incon neat cement. Pull pipe to 3850' after cement job & circ. out excess cement. Pressure test 7" csg. w/1800# and repair if necessary. Drill 6 1/4" hole to 6800' TD w/fresh water. Run Gamma Ray survey surface to TD. Run GR-Sonic & IES surveys 4250 to TD. Set 2750' of 15# J-55 5" liner 4050 to 6800'. Cement 5" liner w/300 sz Incon 4% Gel tailed in with 75 sz Incon neat cement. Circ. cement behind 5" liner. Test top of 5" liner w/1200# for 15 mins. Run GR collar log top of 5" liner to TD & perforate Lower San Andres and Ieso formations at intervals indicated by surveys. Test and attempt completion in both formations.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Soceny Mobil Oil Company, Inc.

Company or Operator

By.....

Position Group Supervisor

Send Communications regarding well to:

Name Soceny Mobil Oil Company, Inc.

Address Box 2406, Hobbs, New Mexico