Submit 3 Copies to Appropriate District Office

APPROVED BY_

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office	bhorgy, witherars and reacur	ar Resources Department	L	Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs NM 88240	OIL CONSERVAT		WELL API NO.	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mex		30-025-02128 5. Indicate Type of Lea	
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410				STATE X FEE
			6. State Oil & Gas Leas	e No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit	Agreement Name
1. Type of Well:	2-101) FOR SUCH PROPOSALS.)		BRIDGES STATE	•
OIL WELL SAS WELL	OTHER			
Name of Operator MOBIL PRODUCING TX & NM	NC.* *MOBIL EXPLORATION {	PRODUCING	8. Well No. 95	
3. Address of Operator AS AGENT FOR MPTM, BOX 633, MIDLAND, TX 79702			9. Pool name or Wildcar VACUUM BLINEB	BRY
4. Well Location Unit Letter P 806	Feet From The NORTH	Line and 660	Feet From The	
Section 26	Township 17-S	Range 34-E		
		ether DF, RKB, RT, GR, et	NMPM LEA	County
11. Check Ar	propriate Box to Indica	te Nature of Notice	Papart or Other	. D. 4-
NOTICE OF IN	TENTION TO:		SEQUENT RE	
PERFORM REMEDIAL WORK	PLUG AND ABANDON X	1		_
TEMPORARILY ABANDON	CHANGE PLANS	1	F	RING CASING
PULL OR ALTER CASING	CHANGE PLANS	COMMENCE DRILLING		AND ABANDONMENT
OTHER:	_	CASING TEST AND CE	MENT JOB []	
		OTHER:		
 Describe Proposed or Completed Ope work) SEE RULE 1103. 	rations (Clearly state all pertinent of	details, and give pertinent dat	tes, including estimated da	te of starting any proposed
SEE ATTACHED PROCEDURE AN	ID WELLBORE SKETCHES OF	N SUBJECT WELL.		
WELL CURRENTLY UNSUCESSE	FUL COMPLETION IN BLINBRY	WITH NO FUTURE UTIL	_ITY	
I hereby certify that the information above is tru	le and complete to the box of			
SIGNATURE HALVII OLLEC	D- 4110		NA HOLA AL	
TYPE OR PRINT NAME KAYE POLLOCK-	f = f + f	ITLE ENV. & REG. TECH		те 09-29-94
			ТЕСЕРНО	NE NO. 915-688-2584
្តី នៃ ្ត្រី	N CIGNEO BY 15 NATON DIREP, II		oc	T 0 4 1994

_____ TITLE _

_____DATE

BRIDGES STATE # 95 VACUUM (BLINEBRY) FIELD LEA COUNTY, NEW MEXICO

RECOMMENDED WORKOVER PROCEDURE

- 1. MIRU PU. DIG PIT. FLOW WELL BACK TO PIT. ND WH. NU BOP.
- 2. POOH W/ 218 JTS 2-3/8" TBG & LD.
- 3. RIH W/ 7" CIBP ON 2-3/8" TBG & SET @ 6250'. STING OUT OF CIBP & CAP W/ 20 SX CLASS C NEAT CMT PLUG FROM 6250-6150'.
- 4. POOH W/ TBG LD UP TO 4450'. MIX & PUMP 50 SX CLASS C NEAT CMT PLUG FROM 4450-4244' ACROSS 7" CSG SHOE @ 4400' & SAN ANDRES TOP @ 4294'.
- 5. POOH W/ TBG LD UP TO 2705'. MIX & PUMP 25 SX CLASS C NEAT CMT PLUG FROM 2705-2605' ACROSS SALT BASE @ 2655'.
- 6. POOH W/ TBG LD UP TO 1760'. MIX & PUMP 25 SX CLASS C NEAT CMT PLUG FROM 1760-1660' ACROSS SALT TOP @ 1710'.
- 7. POOH W/ TBG LD UP TO 408'. MIX & PUMP 25 SX CLASS C NEAT CMT PLUG FROM 408-308' ACROSS 13-3/8" CSG SHOE @ 358'.
- 8. POOH W/ TBG LD. ND BOP. RBIH W/ 1 JT TBG TO 30'. SPOT 10 SX CLASS C NEAT CMT PLUG FROM 30'-SURFACE. POOH W/ WS.
- 9. ND BOP. RD PU. DIG OUT CELLAR AND CUT CSG 3' BELOW SURFACE. WELD STEEL PLATE ON CSG STUB. ERECT P&A MARKER WITH WELL NAME AND PLUGGED DATE. FILL CELLAR AND CLEAN SURFACE LOCATION.

GL - 4003' KB - 13' AGL

BRIDGES STATE # 95 VACUUM (BLINEBRY) FIELD LEA COUNTY, NEW MEXICO CURRENT COMPLETION

P, 26, T 17-S, R 34-E, 860' FSL, 660' FEL

13-3/8" 48# H-40 CSG @ 358' CMT'D W/ 350 SX CIRC.

9 5/8" 40# J-55 ST&C CSG @ 4400' CMT'D W/ 3600 SX CIRC.

7" CIBP @ 6640'
BOT TYPE C MODEL LINER HANGER @ 8149'
5-1/2" CIBP @ 8250' W/ 20' CMT CAP
5-1/2" BAKER "AD-1" PKR @ 8330'


5-1/2" CIBP @ 8620'

5-1/2" CIBP @ 11898' CAPPED W/ 35' CMT 5-1/2" BAKER "N" PERMAMENT PKR @ 11905'

5-1/2" 17# N-80 FL-4S FJ CSG @ 12500' CMT'D W/ 250 SX CIRC.

7" 23, 26, 29, 32# N-80 CSG @ 13816' CMT'D W/ 2750 SX CIRC.

	<u>7" CSG</u>
<u>WT.</u>	DEPTH
23#	0-6628'
26#	6628-9243
29#	9243-12085
32#	12085-13816'



PBTD=6640' TD=13816'

218 JTS 2-3/8" TBG @ 6633'

Blinebry Perfs

6350-6370', 20 ft, 41 holes 6380-6402', 22 ft, 45 holes 6416-6460', 44 ft, 89 holes 6477-6496', 19 ft, 39 holes 6500-6524', 24 ft, 49 holes Tight spot @ 6987'

Abo Perfs

8362-8451' sqz'd w/ 250 sx, did not hold 8360-8520' OA, 1 jspf 9070-9199' sqz'd w/ 250 sx, did not hold

Wolfcamp Perfs

9518-9986' OA, 103 holes, sqz'd w/ 250 sx

Penn Perfs

11112-11122' 11 holes, sqzd w/ 70 sx

Devonian Perfs

12024-12199' OA, 4 jspf, 411 holes

CIBP @ 12500' w/ 50' cmt cap

McKee Perfs

13698-13750

GL - 40031 KB - 13' AGL

BRIDGES STATE #95 VACUUM (BLINEBRY) FIELD LEA COUNTY, NEW MEXICO PROPOSED COMPLETION

P, 26, T 17-S, R 34-E, 860' FSL, 660' FEL

13-3/8" 48# H-40 CSG @ 358' CMT'D W/ 350 SX CIRC

9 5/8" 40# J-55 ST&C CSG @ 4400' CMT'D W/ 3600 SX CIRC.

7" CIBP @ 6640' BOT TYPE C MODEL LINER HANGER @ 81491 5-1/2" CIBP @ 8250' W/ 20' CMT CAP 5-1/2" BAKER "AD-1" PKR @ 8330'


5-1/2" CIBP @ 8620'

5-1/2" CIBP @ 11898' CAPPED W/ 35' CMT 5-1/2" BAKER "N" PERMANENT PKR @ 11905

5-1/2" 17# N-80 FL-4S FJ CSG @ 12500' CMT'D W/ 250 SX CIRC.

7" 23, 26, 29, 32# N-80 CSG @ 13816' CMT'D W/ 2750 SX CIRC.

	<u>7" CS</u> G
<u>WT.</u>	DEPTH
23#	0-6628
26#	6628-9243
29#	9243-12085
32#	12085-13816'



PBTD=6640 TD=13816

10 SX CL C NEAT CMT PLUG FROM 30'-SURFACE

25 SX CL C NEAT CMT PLUG 408-308' ACROSS 13-3/8" CSG SHOE @ 358'

25 SX CL C NEAT CMT PLUG 1760-1660' ACROSS SALT TOP @ 1710'

25 SX CL C NEAT CMT PLUG 2705-2605' ACROSS SALT BASE @ 2655'

50 SX CL C NEAT CMT PLUG 4450-4244' ACROSS 9-5/8" CSG SHOE @ 4400' & SAN ANDRES TOP @ 4294'

7" CIBP @ 6250' W/ 20 SX CL C NEAT CMT CAP

Blinebry Perfs

6350-6370', 20 ft, 41 holes 6380-6402', 22 ft, 45 holes 6416-6460', 44 ft, 89 holes 6477-6496', 19 ft, 39 holes 6500-6524', 24 ft, 49 holes Tight spot @ 6987'

Abo Perfs

8362-8451' sqz'd w/ 250 sx, did not hold 8360-8520' OA, 1 jspf 9070-9199' sqz'd w/ 250 sx, did not hold

Wolfcamp Perfs

9518-9986' OA, 103 holes, sqz'd w/ 250 sx

Penn Perfs

11112-11122' 11 holes, sqz'd w/ 70 sx

Devonian Perfs

12024-12199 OA, 4 jspf, 411 holes

CIBP @ 12500' w/ 50' cmt cap

McKee Perfs

13698-13750'