

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITARY	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR NOTICES TO WELL OWNERS CONCERNING WELL CORKS TO A DIFFERENT RESERVOIR. USE APPLICABLE FORM FOR PERMIT TO DRILL OR RE-ENTER EXISTING WELL FOR A DIFFERENT RESERVOIR.		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. B-10860
1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- Water Injection Well 2. Name of Operator Atlantic Richfield Company 3. Address of Operator P. O. Box 1710, Hobbs, New Mexico 88240 4. Location of Well UNIT LETTER I 2310 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 31 TOWNSHIP 17S RANGE 34E NMPH. 13. Elevation (Show whether DF, RT, GR, etc.) 4072' GR		7. Unit Agreement Name 8. Form or Lease Name State Vacuum Unit 9. Well No. 11 10. Field and Pool, or Wildcat Vacuum Grbg SA 12. County Lea


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☒ Run Liner, cmt, perf, acidize & Convert to WIW

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Rigged up on 1/18/77. POH w/rods & pump, inst BOP & POH w/tbg. CO hole to 4715' PBD. Ran Caliper log 4776-4378'. RIH w/3 1/2" 10R 9.2# liner & liner hanger assy, set liner @ 4762'. Top of liner @ 4242'. Cmt'd liner w/20 bbls gel cont'g 25# WG-11 & 8 1/2 gal Parasperse followed by 105 sx Cl H batch mix w/4.3# salt, 1/4# flocele & 1% HLX-C204. Displ plug w/18 B.V. Bumped plug w/800#. Rel liner setting tbg & POH. WOC 18 hrs. Press tstd liner to 1000# 30 mins OK. New PBD 4810'. Ran GR-N log 2800-4813', Caliper log 4250-4800' & Csg Inspection log 4300'FS. Ran CBL & GR-Corr log, indicated TOC @ 4418'. Cmt'd top of liner @ 4242' w/50 sx Cl H w/1% HLX & 4.3# salt/sk followed by 50 sx Cl C w/3# salt & .3% Halad 22A. WOC. POH w/cmtg tool & tbg. Drld TOC inside 5 1/2" csg to top of liner @ 4242'. Drld cmt inside 3 1/2" liner to 4767'. Circ hole clean. Perf'd 4693-4734' w/1 JSPF. VIH w/seal assy on 2-3/8" OD EUE internally plastic coated tbg, set in PBR @ 4242'. Press tstd csg annulus to 1000# 30 mins OK. Trtd San Andres perms 4693-4734' w/2000 gals 15% HCL-NE acid w/iron sequestrant. Flushed w/100 BFW. MP 1400#, Min 100#, ISIP 50#, vac in 30 sec. Well shut in. Converted to WIW eff 2/9/77. NMOCC to be notified when water injection commences.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	TITLE Dist. Drlg Supt.	DATE 2/14/77
APPROVED BY Jerry Seaton	TITLE Dist. Drlg Supt.	DATE 2/14/77
CONDITIONS OF APPROVAL, IF ANY:		