

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. 30-025-02196
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: West Vacuum Unit
8. Well No. #32
9. Pool name or Wildcat Vacuum, Grayburg, San Andres
10. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other ☐ Injector ☐
2. Name of Operator
Texaco Exploration & Production, Inc.
3. Address of Operator
P. O. Box 3109, Midland, TX 79702
4. Well Location

Unit Letter O : 660 feet from the South line and 1980 feet from the East line

Section 33 Township 17S Range 34E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- Set 5 1/2 CIBP @ 4350' spot 25 Sx plug 4350'-4150' (Grayburg-San Andres) Tag @ 4118'
- Displace hole w/MLF, 9.5# Brine w/25# gel P/BBL
- Spot 25 Sx plug 3800'-3600' (Queen)
- Spot 25 Sx plug 2900'-2700' (Yates, B-Salt) Tag @ 2603'
- Spot 25 Sx plug 1700'-1500' (T-Salt) Tag @ 1442'
- Perf 6 holes @ 960' sqz w/125 Sx plug 960'-700' (8 5/8" shoe) Tag @ 695'
- Circ Cmt 30' to Surf w/15 Sx, Install dry hole marker. 09/11/01

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jimmy Bagley TITLE MANAGER DATE 9/11/01

Type or print name Jimmy BAGLEY Telephone No. 915 683-4996

APPROVED BY Johnny Polina TITLE DATE NOV 30 2001

Conditions of approval, if any:

GW

dm

