## NEW MEXICO OIL CONSERVATION COMMISSION

## Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin, A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Eclow

Notice of Intention to Chance Plans		NOTICE OF INTENTION T TEMPORARILY ABANDON	Notice of Intention to Temporarily Abandon Well		Notice of Intention to Drill Deeper			
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention to Plug Back	Notice of Intention to Plug Back		Notice of Intention to Set Liner			
Notice of Intention to Squzzze		NOTICE OF INTENTION TO ACIDIZE			Notice of Intention to Shoot (Nitro)			
NOTICE OF INTENTION TO GUN PERFORATE		Notice of Intention (Other)	frac		Notice of Intention (Other)			
OIL CON Santa Fi	SERVATION COMMISS 2, NEW MEXICO	Hobbs, New 1	lexico		Aoril 15	, 1963		
Gentlemen	:				(2200)			
Follow	ving is a Notice of Intentio	on to do certain work as described	L					
	CACC Inc.	Maria da como como como como como como como com						
	i Port the time of	State of NM "V"	*()	Well No		L	·····	
247) 	.14 SW	<u>34</u> , T. <u>17-S</u> , R.	30-E KA	DVG	Vacuum	(Unit)		
			••••••	IFM.,			Pool	
	}	County.						
	(FC	FULL DETAILS OF PROP PLICW INSTRUCTIONS IN TR	POSED PLAI HE RULES AN	N OF WORK	()NS)			
We		e following work on su						
1.	Inject a mixture into the tubing	e of 55 gals of cheple casing annulus after	x in 500 g pumping we	als of 5% h ll down.	ydrochloric	acid		
2.	After a period of 24 hours, pull rods and tubing.							
3.	Clean out to total depth if necessary.							
4.	Fracture open hole section from 4135' to 4700' in 3 stages each of 10,000 Gals refined oil carrying one 1b of sand per Gal, with 1000 1bs of flaked naphthalene between stages down 3 inch tubing with hook wall packer set at 4100'.							
5.	Recover load oil	, test, return well t	o producti	on.				
Approved Except as follows:				TEXAC	) Inc.			
		В	y	, Company	er Operator			
				·.	1. *			

Approved

 $2\gamma$ 

Tide.

OIL CONSE

11

ATION ECVENISSION

Position Assistant District Superintendent Send Communications regarding well to:

Name J. G. Blevins, Jr.

Address P. O. Box 728, Hobbs, New Mexico