NEW MF **OO OIL CONSERVATION COMMI** Ν

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

DIL CONSERVATION COMMISSION, anta Fe, New Mexico. Sentlemen: You are hereby notified that it is our inter	Place DUPLICATE
You are hereby notified that it is our inter	ntion to commonae the drilling of a well to be brown as
	ntion to commence the drifting of a well to be known as
Geo. F. Getty, Inc.	- State "F" Well No. 4 in CNE NW
f Sec. 36, T. 17, R. 34	Lease Field, Lease County.
	s 660 feet (X.) (S.) of the North line and 1980 feet
(E.) (E.)	of the West line of Section 36 -
(Give locati	ion from section or other legal subdivision lines. Cross out wrong directions.)
	d the oil and gas lease is No. B-1565 , Assignment No.
If patented	land the owner is
Address	
	nent land the permittee is
Address	
The lessee	is Geo. F. Getty, Inc.
	Jersey City New Jersey
AREA 640 ACRES	e to drill well with drilling equipment as follows:
Rotary tools fro	m top to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:_____

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Size of Hole Casing	Weight Per Foot	New or Secoud Hand	Depth	Landed or Cemented	Sacks Cement
16" 13" 12" 9-5/8" 8-1/4" 7"	40# 36# 24#	Second Hand New	2601 15201 41001	¢emented ¢emented ¢emented	200 3 00 3 99

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4150*

Additional information:

In setting and cementing the 13" OD surface casing the cement will be circulated back into the cellar by Halliburton Process. At each time casing is set and cemented sufficient time shall be allowed for cement to thoroughly set before drilling plug and testing. _. 19____ Sincerely yours. Annroved

		· · · · · · · · · · · · · · · · · · ·
except as follows:	DEC 1 3 1938	Skelly Oil Company - Operator for
		eo.F. Getty, Inc.
		By K/imlary
		Position District Superintendent
		Send communication regarding well to
-V.	RVATION COMMISSION	Name Skelly Obl Co.
	& CAS INSPECTOR	Address Hobbs, New Mexico

2 • •



. مراجع المراجع الم

.