PLUGGING INTENTION REFORT

RICHARDSON & BASS

, manager - Linkston

Julia Brainard No. 1- 1980 feet from South line and 660 fest from East Line of Section 19, Township 19-S, Range 34-E, Lea County, New Mexico- "Mildcat".

> Total Depth 5010 feet. Hole filled with mud ladened fluid.

Will spot 180 sacks cement at 4955 Feet to cover drill stem tests zones from 4665-4820 and 4811-4905.

Will spot 110 sacks coment at 4050 feet to covar drill stem test zone from 3872 to 4000 feet.

Will spot 150 sacks cement at 3550 feet to cover drill stem test zone from 3342 to 3550 feet. 9-5/8" casing is set at 3342 feet and enough cement will be spotted to cover the drill stem test zone and 50 feet inside of the bottom of 9-5/8" casing.

The 9-5/8" casing will be knocked off at approximately 570 feet (This is the top of the cement behind the casing) and the pipe will be pulled. Will spot 50 sacks comment on top and inside of 9-5/8" casing where knocked off.

Will spot 25 sacks of cement in top of 13-3/8" casing at the surface.

The pits and cellar will be filled and the location levelled. The marker as required will be placed alongside the 13-3/8" casing.

RICHARDSON & BASS Br- Car annye Superint andent