

(SUBMIT IN TRIPLICATE)

Land Office **Santa Fe**
Lease No. **NM 086**
Unit _____UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 14th, 1958

Well No. 1 is located 660 ft. from XX line and 660 ft. from E line of sec. 25
SE 1/4 of Sec. 25 19-S 34-R NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3746 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well to be spudded by July 20th, 1958. Will set 300 feet of 8-5/8" 24# casing and cement with 225 sacks, sufficient to circulate. Well to be drilled to depth of 5200 feet, to test the Queen Sand at approximately 4800 feet and the Penrose Sand at approximately 5100 feet. If commercial production encountered will set 5-1/2" 15.50# casing for oil string and cement according to specifications. Will mud up with jet mud before spudding and will mud up at about 5100 feet with 15 water loss and 45 viscosity mud.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company FORSTER DRILLING COMPANYAddress P. O. Box 588Odessa, TexasBy Edmond G. King
Title Agent

The approval is subject to the following conditions:

1. Obtain approval of this office as to the amount of cement to be used on the $5\frac{1}{2}$ " casing before cementing operations are commenced.