## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

		Indicate Nature		
REPORT ON BEGIN DRILLING OPERAT	NING TONS	REPORT ON OF CASING	RESULT OF TEST SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESUI OF PLUGGING WEI	LT X	REPORT ON OPERATION	RECOMPLETION	REPORT ON (Other)
		<b>P</b>	ebruary 16, 1954	Hobbs, New Mexico
Following is a rep	port on the work done	e and the results ob	stained under the heading	noted above at the
Stanolind Oi	Company or Operator	any		State AF
Lea County C	asing Pullers (Contractor)		, Well No <b>1</b>	in the SE 1/4 ME 1/4 of Sec 3
				<b>Los</b> Cour
				pary 12, 1954 Inclusive
			Form C-102 on	(Cross out incorrect words)
lugging was com	DETAILED pleted on Febru  SX. OF CEME	ACCOUNT OF WO	ORK DONE AND RESU	LTS OBTAINED  Igs set at the following interv
	DETAILED pleted on Febru	ACCOUNT OF WO	All intervals laden fluid. Approximately A 4" pipe mark ground level. surface restor	were filled with heavily mud  620' of 9-5/8" casing was puller was set to extend 4' above  Pits will be filled and grounded to conform with surrounding pplemental report will be filed
EPTHS  1000 - 12585' 1457 - 10130' 1955 - 6690' 1945 - 4885' 620 - 590' 1946 - Witnessed by	DETAILED pleted on Febru  SX. OF CEME  150 sx. \( \frac{1}{50} \) 150 sx. \( \frac{1}{20} \) 25 sx. 20 sx. 10 sx.	ACCOUNT OF WO	All intervals laden fluid. Approximately A 4" pipe mark ground level. surface restor terrain. A su when this work  olind Oil and Gas	were filled with heavily mud  620' of 9-5/8" casing was puller was set to extend 4' above Pits will be filled and grounded to conform with surrounding pplemental report will be filed is completed.  Company  Farm Boss  (Title)
EPTHS  1000 - 12585! 1457 - 10130! 1955 - 6690! 1945 - 4885! 1620 - 590! 17fage -	DETAILED pleted on Febra  SX. OF CEME  150 sx. / 50 150 sx. / 20 25 sx. 20 sx. 10 sx.	ACCOUNT OF WO	All intervals laden fluid. Approximately A 4" pipe mark ground level. surface restor terrain. A su when this work  Clind Oil and Gas (Company)  I hereby certify that to the best of my known that the second my known that t	were filled with heavily mud  620' of 9-5/8" casing was puller was set to extend 4' above  Pits will be filled and grounded to conform with surrounding pplemental report will be filed is completed.  Company  Farm Bose  (Title)
EPTHS  1000 - 12585! 1457 - 10130! 1955 - 6690! 1945 - 4885! 1620 - 590! 17face -	DETAILED pleted on Febru  SX. OF CEME  150 sx.   50 150 sx.   20 25 sx. 20 sx. 10 sx.	ACCOUNT OF WO	All intervals laden fluid. Approximately A 4" pipe mark ground level. surface restor terrain. A su when this work  Olind Oil and Gas (Company)  I hereby certify tha to the best of my ki	were filled with heavily mud  620' of 9-5/8" casing was puller was set to extend 4' above  Pits will be filled and grounded to conform with surrounding pplemental report will be filed is completed.  Company  Farm Bose  (Title)