NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable," or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper Notice of Intention to Set Liner		
Notice of Intention to Plug Well	x	Notice of Intention to Plug Back			
OTICE OF INTENTION		Notice of Intention			
O SQUEEZE TO ACIDIZE		to Shoot (Nitro)			
Notice of Intention		Notice of Intention	Notice of Intention		
to Gun Perforate		(Other)	(Other)		

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Hobbs, New Mexico

November 25, 1952

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Stanolind Oil and Gas Company

(Place)

	State "V (Company or)						Well No	1	in	H
SE 1/4 NE			т 17	, ,	35		Nant To			(Unit)
(40-acre Subdivision)		••••••••••••••••••••••••••••••••••••••	, I	, K .		,NMPM.,	Heat DO	VIIgcon	•••••	Pool
7										

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The above well was drilled to a total depth of 5225' and completed 10/31/49. At the time of completion this well produced by pump, 23 barrels oil and 31 barrels of water in 24 hours. During January and February 1950, production had dropped to approximately 4 barrels oil and 10 barrels water per day. By June 1950 the well was producing no oil or gas and a very slight amount of water.

We propose to plug and abandon this well as follows: Load hole w/10# mud. Shoot off and pull approximately 3100' of $5\frac{1}{2}$ " casing and spot 25 sack cement plugs as follows: In top of $5\frac{1}{2}$ " casing stub (3100'); at 2025' (base of salt and at bottom of 8-5/8" intermediate string); and at the surface.

The location will be restored to its original contour and a 4" abandonment pipe marker will be installed to conform with existing New Mexico Oil Conservation Commission regulations.

Approved		10
Except as follows:	······,	19

Stanolind O	1 and	Gas	Company	
By				
	1			

Position Field Superintendent Send Communications regarding well to:

Name Ralph L. Hendrickson

Address. P.O. Box 68 - Hobbs, New Mexico