

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Sept. 5, 1949

Box 670, Roswell, N.M.

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Barnett & Rector State "C" Well No. 1 in the \_\_\_\_\_  
Company or Operator Lease  
N.W. SE. of Sec. 19, T. 17 S., R. 35 E, N. M. P. M.,  
Vacuum Field, Lea County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on Aug. 15, 1949  
oral and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On Aug. 21, 1949, 8 5/8" OD 28# J-55 casing was run to 1786' and cemented by Halliburton with 75 sacks of cement. Then 1" pipe was run outside the casing to a depth of 250', and 125 sacks of cement was circulated thru this 1" pipe and back to the surface.

The rotary drilling equipment was moved off the location and a Jumbo "J" Spudder moved in. The cement plug was drilled and test made for water shut-off on August 28, 1949. After bailing the hole dry and allowing to set four hours, no water appeared in the hole.

Witnessed by Clyde Hicks Sam Sanders Drilling Supt.  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_  
5th day of September 1949  
W. H. Douglas  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name John A. Barnett  
Position Co-Partner  
Representing Barnett & Rector  
Company or Operator

My commission expires 10/24/55

Address Box 670, Roswell, New Mexico.

Remarks:

Ray G. G. G. G.  
Name  
Title