

Santa Fe, New Mexico

CORRECTED
NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

P.O. Box 670, Roswell, New Mexico August 18, 1949

Place

Date

OIL CONSERVATION COMMISSION,
 Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Barnett & Rector

State

well No. **1-C**in **NW 1/4 SE 1/4**

Company or Operator

Lease

of Sec. **19**, T **17 S**, R **35 E**, N. M., P. M., **Vacuum** Field, **Lea** County.

N

The well is **1980** feet (N.) (~~S~~) of the **South** line and **2310** feet (E) (W.) of the **East** line of **Section 19**

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. **B-1398** Assignment No. _____

If patented land the owner is _____


Address _____

If government land the permittee is _____

Address _____

The lessee is _____

Address _____



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary to about 1800'; Cable tools from about 1800' to about 4700' (Total depth)

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: **Blanket bond being submitted**

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
(0-250) 13"						(75 on bottom & 100 from 250' back to surface)
(250-1800) 11"	8 5/8"	28#	New	1800	Cemented	
	7" OD	20#	New	4400	Cemented	75

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about **4450** feet.

Additional information: **The 8 5/8" casing will be cemented with not less than 75 sacks of cement at the bottom; then a string of small pipe will be run down to 250' on the outside of the 8 5/8" casing, and cement circulated from that point on back to surface. (THIS CORRECTED DRILLING APPLICATION REPLACES ONE SUBMITTED BY BARNETT & HANSON DATED JUNE 28, 1948 AND APPROVED JULY 5, 1949.)**

Approved

Sincerely yours,

except as follows: SEP 6 1949

BARNETT & RECTOR

Company or Operator

By

John A. Barnett

Position

Co-owner

Send communications regarding well to:

Name

Barnett & Rector

Address

**P.O. Box 670,
Roswell, New Mexico**

OIL CONSERVATION COMMISSION,

By

Title