

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Box 670,

Roswell, New Mexico,

June 28, 1949.

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Barnett &amp; Hanson

State

well No. 1-C

in NW 1/4 SE 1/4

Company or Operator

Lease

of Sec. 19, T. 17 S., R. 35 E., N. M., P. M., Vacuum Field, Lea County.

N

The well is 1980 feet (N.) of the South line and 2310 feet (W.) of the East line of Section 19

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-1398 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_


Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_



AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

Rotary to about 1800'; Cable tools from about 1800' to about 4700' (Total depth)

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: Blanket bond already on file.

We propose to use the following strings of casing and to land or cement them as indicated:

| Size of Hole   | Size of Casing          | Weight Per Foot | New or Second Hand | Depth | Landed or Cemented | Sacks Cement                                   |
|----------------|-------------------------|-----------------|--------------------|-------|--------------------|--|
| (0-250) 13 3/4 | 8 5/8"                  | 28#             | S.F.               | 1800  | Cemented           | (50 on bottom & 100 from 250' back to surface) |
| (250-1800) 11" | 5 1/2" OD<br>(or 7" OD) | 15 1/2#         | New                | 4400  | Cemented           | 75   |

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4450 feet.

Additional information: The 8 5/8" casing will be cemented with not less than 50 sacks of cement at the bottom; then a string of small pipe will be run down to 250' on the outside of the 8 5/8" casing, and cement circulated from that point on back to surface.

Approved JUL 5 1949, 19 \_\_\_\_\_

except as follows: If 1" pipe fails to come back to 250' depth, 8 5/8" casing must be two staged at the 250' depth.

Sincerely yours,

BARNETT &amp; HANSON

Company or Operator

By

John A. Barnett

Position

Co-Partner

Send communications regarding well to:

Name Barnett &amp; Hanson

P.O. Box 670,

Address Roswell, New Mexico.

By

Title

OIL CONSERVATION COMMISSION