

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Box 670,

Roswell, New Mexico

Mar. 11, 1950

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Barnett & RectorState "C"well No. 2in SE 1/4

Company or Operator

Lease

of Sec. 19, T. 17 S., R. 35 E., N. M. P. M., Vaduz Field, Lea County.

N

The well is 330 feet (N.) ~~W.~~ of the South line and 330 feet ~~W.~~ (W.) of the East line of Sec. 19

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-1398 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

Rotary to about 1800'; Cable tools from about 1800' to about 4700'

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: Blanket bond already filed

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
( 0- 250) 13"	8 5/8"	28#	New	1800	Cemented	(75 on bottom & 100 from 250' back to surface)
(250-1800) 11"	8 1/2"	20#	New	4350	Cemented	100

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4450 feet.

Additional information: The 8 5/8" casing will be cemented with not less than 75 sacks of cement at the bottom; then a string of 1" pipe will be run down to 250' on the outside of the 8 5/8" casing, and cement circulated from that point on back to surface.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

Sincerely yours,

Barnett & Rector

Company or Operator

By \_\_\_\_\_

John A. BarnettPosition Agent

Send communications regarding well to:

Name Barnett & Rector,

Box 670,  
Address Roswell, New Mexico

OIL CONSERVATION COMMISSION,

By \_\_\_\_\_

Title \_\_\_\_\_