NEW MEXICO OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

SUBMIT THIS NOTICE IN TRIPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORLD SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLANS SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

NOTICE OF INTERTION DO CHANGE FLANS OTHICE OF INTERTION DO PURE WELL OTHICE OF INTERTION DO FUND ACCOUNTY OF SECURITY OF INTERTION DO SAUGEST OF INTERTION TO PURE DACK OTHER STORM OTHER STORM OF INTERTION DO SAUGEST OF INTERTION TO ACCIDE TO SAUGEST INTERTION TO ACCIDE TO SAUGEST TO SHOOT (NUTRO) OTHER STORM OTH			ATE NATURE OF NOTICE	DI CRECKING	BELOW			
TO PULL DETAILS OF PROPOSED PLAN OF WORK FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTION) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Full Details of proposed plug from 700 to 900. (There are holes in the 5½-inch casing: 779 to 364.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. PPROVED PROVED NOTICE OF INTENTION NOTICE OF INTENTI								
TO SALEZE TO ALDIE TO SHOOT (NITRO) OTICE OF INTENTION NOTICE OF INTENTION NOTICE OF INTENTION OTICE OF INTENTION NOTICE OF INTENTION OTICE OF INTENTION NOTICE OF INTENTION OTICE OTICE OF INTENTION OTIC		x		1 11				
COUNSERVATION COMMISSION ANTA FE, NEW MEXICO Hobbs, New Mexico (FLACE) FOLICWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW/ AT THE Mumble Oil & Refining Company, N.M. State J NW 1/2 OF SEC. TOWNSON Lea COUNTY. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLICW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing section of the 5½-inch casing with a mud laden fluid. Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMOCC. PPROVED NOTE: Offset operators notified by letter March 11, 1957. PPROVED NOTE: OFFSET OPERATOR BY MARCH COMPANY OF COMPANY O					14 · · · · · · · · · · · · · · · · · · ·			
ANTA FE, NEW MEXICO (RACE) (
FOLICWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE Mumble Oil & Refining Company, N.M. State J WELL NO. 2 IN L (COMPANY OR OPERATOR) NW 1/2 OF SEC. 17 OF TITTS, R 35E, NMPM. Vacuum (UNIT) FULL DETAILS OF PROPOSED PLAN OF WORK (FOLIOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing 1779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMCCC. PPROVED THUMBLE OIL & Refining Company COMPANY OF COMPANY O		AISSION	Hobbs, New Me	xi c o		3-11 -57		
FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW! AT THE Mumble Oil & Refining Company, N.M. State J WELL NO. 2 IN L NW N SW 1/4 OF SEC. 19 OF OPERATOR, TO SEC. 19 OF OPERATOR, TO SEC. 19 OF SEC.	cniti elagni.		(PLACE)			(DAT)	E)	
Numble Oil & Refining Company, N.M. State J NW N SW N OF SEC. 19 OF OPERATOR) R. 35E, NAMPM., Vacuum (UNIT) (40-ACRE SURDIVISION) Lea COUNTY. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing 779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMCCC. PPROVED NOTE: Humble Oil & Refining Company COMPANY OF COMPANY O								
NW 14 SW 14 OF SEC 17 T 17S R 35E NAPPM., Vacuum PC (40-ACRE SURDIVISION) Lea COUNTY. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing: 779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMCCC. PPROVED 19 Humble Oil & Refining Company COMPANY OF COSPANOR BY MARCH COMPANY OF COSPANOR WELL TO.								· · · · · · · · · · · · · · · · · · ·
COUNTY. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing : 779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMCCC. PPROVED 19 Humble Oil & Refining Company COMPANY OF COMPA	umble Cil & Refining C		OR OPERATORI					IINOT)
COUNTY. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing: 779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMOCC. PPROVED Thumble Oil & Refining Company COMPANY OF COMPANY	NW 14 SW 14 OF	F SEC. 19	T_178 R_	35E , NMPM.		Vacuum		PO(
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Set a cast iron bridge plug at 3860 and dump 10 feet of cement on top. Fill the 5½-inch casing with a mud laden fluid. Spot a 200-foot cement plug from 700 to 900. (There are holes in the 5½-inch casing: 779 to 804.) Place a 10-foot cement plug in top of the 5½-inch casing. Remove wellhead. Place marker over well as required by the NMOCC. The set of th		201						
PPROVED	Spot a 200-foot ce 779 to 804.) Place a 10-foot ce Remove wellhead.	ement plu	ag from 700 to 900. ag in top of the $5\frac{1}{2}$	(There are he inch casing,		in the 5½-i	nch ca	sing f
PPROVED SEND COMMUNICATIONS REGARDING WELL TO								
PPROVED SEND COMMUNICATIONS REGARDING WELL TO	PPROVED	rs notifi	-	Humble			npany	
	PPROVED	rs notifi	-	Humble			npany	
	PPROVEDKCEPT AS FOLLOWS:	rs notifi	, 19 BY	Humble	COMPANY	OR COSTRATOR	7	

ADDRESS_

TITLE

Box 2347, Hobbs, N.H.