

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Roswell, New Mexico

Aug. 27, 1948

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Barnett & Hanson

State

Well No. 1-Bin NW1/4

Company or Operator

Lease

of Sec. 19, T. 17S, R. 35E, N. M., P. M., Vacuum Field, Lea County.

N

The well is 990 feet (N) (S) of the North line and 330 feet  
(E) (W) of the West line of Sec. 19

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-8290 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary to about 1750'; Cable tools to about 1750' to total depth (about 4700')

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \$10,000 Blanket Bond Form 39-A1 (being sent directly to State

Geologist at Santa Fe, N.M.)

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17"	12 3/4"	36#	S.H.	240	Cemented	100 (Circulated)
11"	8 5/8"	28#	S.H.	1750	(Set & Pull)	(Mud)
8"	7"	20#	New	4300	Cemented	(100 plus)

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4400 feet.

Additional information:

Approved \_\_\_\_\_

SEP 7 1948

19

Sincerely yours,

except as follows:

Barnett & Hanson

Company or Operator

By John A. BarnettPosition Co-Partner

Send communications regarding well to

Name Barnett & HansonBox 1128Address Roswell, New Mexico

OIL CONSERVATION COMMISSION,

By Ray Spunkhoush

Title \_\_\_\_\_

*Return to top of well section  
on 11" casing 3' to 4' cemented  
at top of sand by 2" stuff without*

