## Submit 3 Copies to Appropriate

APPROVED BY-

CONDITIONS OF AFFROVAL, IF ANY:

## State of New Mexico

Form C-103 · Revised 1-1-89

## Energy, Minerals and Natural Resources Department

District Office		
DISTRICT I P.O. Box 1980, Hobbs, NM 88240  DISTRICT II P.O. Drawer DD, Artesia, NM 88210  DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410  SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-02833
		5. Indicate Type of Leese STATE X FEE
		6. State Oil & Gas Lesse No. B-2423-4
		7. Lease Name or Unit Agreement Name
1. Type of Well: OH. GAS WELL X WELL OTHER		East Vacuum Gb/SA Unit Tract 1961
2 Name of Operator Phillips Petroleum Company		8. Well No. 001
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762		9. Pool same or Wildcat Vacuum Gb/SA
4. Well Location  Unit Letter E : 1980 Feet From The North	Line and 660	Feet From The West Line
Service 19 Township 17-S	Range 35-E	NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)		
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB	
OTHER: Swab Test		
<ol> <li>Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent details, including estimated date of starting any proposed work) SEE RULE 1103.</li> <li>MIRU DDU. COOH LD rods (if applicable). NU BOP. Release TAC and COOH with production tubing (if applicable).</li> <li>RIH with casing scraper to +/- 50' above top perforation or openhole interval.</li> <li>RIH w/packer to +/- 50' above top perforation or openhole interval. Set pkr. and load backside to verify casing integrity.</li> <li>Swab test well for 1 day. If decision is made to TA, go to Step 5. COOH ND BOP, RD DDU, and wait on reactivation procedure.</li> <li>COOH with packer. RIH with CIBP on workstring. Set CIBP within 100' of perforated or openhole interval. Fill casing with inhibited fluid containing 1% TH-370 by volume. COOH w/tubing. Pressure test to 500 psi and record chart. ND BOP. RD DDU.</li> </ol>		
I hereby certify that the information above is true and complete to the best of my knowledge and balled.		
SUDV. Regulatory Affairs 05-19-94		
TYPEORPENTNAME L. M. Sanders (915) 168-148		
(This space for State Use)	ORIGINAL SIGNED DISTRICT I	SUPERVISOR TALL 25 1994

- TILE -

**AFCEIVED** 

MAY 23 1994

OFFICE