

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

March 7, 1950

Roswell, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Barnett & Rector State NM Well No. 1 in the \_\_\_\_\_  
 \_\_\_\_\_ Company or Operator Lease \_\_\_\_\_  
SW 1/4 of Sec. 20, T. 17 S., R. 35 E., N. M. P. M.,  
Vacuum Field, Lea County.

The dates of this work were as follows: \_\_\_\_\_

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on Feb. 10, 1950  
 and <sup>oral</sup> approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On Feb. 3, 1950, 7,100,000 cubic feet of non-inflammable gas was encountered at 3861-3863'. Halliburton killed the gas by pumping mud into the hole. On Feb. 12, we ran 7" OD 20# J-55 new seamless casing at 3881', and Halliburton cemented same with 75 sacks of cement. After setting 72 hours, the cement plug was drilled and drilling continued. A gas shut-off was effected, and drilling continued to 4347', where a liner of 5 1/2" OD 15# J-55 new seamless casing was set and cemented by Halliburton on Feb. 26, 1950. The liner was set from 3721' to 4347' and was cemented with 40 sacks of cement, which circulated above the liner and back inside the casing. The cement set 72 hours, and no gas or water appeared after it was drilled.

Witnessed by John A. Barnett Barnett & Rector Agent  
 Name Company Title

Subscribed and sworn before me this 10thday of March, 19 50

Emerson B. Podhunter  
 Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name John A. Barnett  
 Position Barnett & Rector Agent  
 Representing Barnett & Rector

Company or Operator

Box 670,

My commission expires Feb. 28, 1950Address Roswell, New Mexico

Remarks:

Ray Garbrough  
 Name  
 Title

11/11/11

11/11/11

11/11/11

11/11/11

11/11/11

11/11/11

11/11/11