

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

Hobbs, New Mexico

January 26, 1939

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Drilling & Exploration Co., Inc.

State "N"

Well No.

COMPANY OR OPERATOR

LEASE

324 - HW4

of Sec. 22

T. 17-S

R.

35-S

Vernon

Field,

Lee

The dates of this work were as follows: January 22 to 24, 1939

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on January 21 19 39 and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

A solid cement plug consisting of 150 sacks was placed from Total Depth (4690') to 4190' (89' above 5 1/2" casing shoe). The hole was then filled with 27 barrels of heavy drilling mud (1.36 Sp. Gr.) to 3000' at which depth a 10 sack cement plug was placed (3000'-3020'). The 5 1/2" casing was shot off at 2710' and 2603' of 5 1/2" casing recovered. The remaining hole was filled to within 18' of surface with 75 barrels of drilling fluid (Sp. Gr. 1.36) and a 6 sack cement plug placed in the 8 5/8" casing from there to surface. A 4" diameter pipe extending 4' above surface level was left to permanently mark this location.

Casing left in hole: 0-2637' of 8 5/8", 28' casing
2710-4279' of 5 1/2", 17' casing

Work was done under supervision of Lee Brundley, Box 1575, Hobbs, New Mexico.

Witnessed by Marshall W. Meyer, Phillip R. C. Hays, Jr.
Name Company Title

Subscribed and sworn to before me this

27th day of January, 1939
Doris S. Stouff
Notary Public

My Commission expires Aug. 11, 1941

Remarks:

I hereby swear or affirm that the information given above is true and correct.

Name Lodigey

Position Office Manager

Representing Drilling & Exploration Co., Inc.
Company or Operator

Address P.O. Box 1575, Hobbs, New Mexico

R.O. Garbrough
Name

OIL & GAS INSPECTOR

Title